

Cleaning and chemical products











Cleaning and chemical products

Welcome to our FENDT and AGCO Parts cleaning and chemical products catalogue.

The FENDT and AGCO Parts branded products stand for quality and are specially designed for use in agricultural engineering and agriculture.

The extensive range extends from cleaning and maintanence products to antifreeze and skin care.

Visit your local FENDT dealer!

Table of Contents

5	For your sprayer
6	Screen cleaners and frost protectio
7	Vehicle and cabine care
10	Corrosions wax
12	Antifreeze products
16	Fuel-Additives
17	System-Additives
18	Lubricants
20	Cleaners for workshop and vehicles
21	Maintenance products
22	Assessory equipment
23	Spraying equipment
24	Skin care
26	Animal house hygiene

For your baler

For your baler

Baler gear oil CLP ISO 150

Industrial gear oil for agricultural machinery.

Contains high pressure EP additives. Protects against corrosion and oxidation. High thermal and mechanical load. Very good high and low temperature behaviour. Protection against wear. According to CLP DIN 51517/T3, CKD ISO 6743-6.

See page 22 for convenient assessories.



Baler gear oil is available in the following container sizes:

container	part no.
5l canister	X991 601 500 632
20l canister	X991 601 500 631
60l barrel	X991 601 500 633

Baling chain oil CGLP 100

High pressure chain lubricant with adhesive additive. Reduces wear. Especially suitable for sliding and vertical surfaces.

See page 22 for convenient assessories.



Baling chain oil is available in the following container sizes:

container	part no.
5l canister	X991 601 500 312
20l canister	X991 601 500 311
60l barrel	X991 601 500 313



For your sprayer

Organic sprayer cleaner ultra

Biodegradeable power cleaner.

Dissolves and removes chemical and colour residues from pesticides on tractors, wine harvesting machines, sprayers, plastic and metal tanks, machinery and wheel rims easily. Also suitable for the quick cleaning of trucks and cars. Can be used in self-service washing plants, with high pressure washers and spraying equipment. Dries without residue as long as it is properly rinsed off after cleaning.

Mix 1:5 with water.



Organic sprayer cleaner ultra is available in the following container sizes:

container part no.

10kg canister X991 601 500 520

with 1.5 with water.

Sprayer BIO-frost protection green

Biodegradable anti-freeze concentrate based on watery tenside cleaners, alcohol and glycol.

Prevents agricultural sprayers from freezing during winter storage.

Do not use for screens and radiators.



Sprayer BIO-frost protection green is available in the following container sizes:

container	part no.
5l canister	X991 601 075 000
25l canister	X991 601 076 000



Screen cleaners and frost protection

Windscreen antifreeze

For cleaning the front screen in winter.

Undisolved down to -30°C.

Suitable for fan nozzles and polycarbonate glass headlights.

Contains tensides, additives and alcohol.



Windscreen antifreeze is available in the following container sizes:

container	part no.
1l bottle	X991 601 500 381
5l canister	X991 601 500 383
25l canister	X991 601 500 382

Summer window cleaner 1:10

Screen cleaning concentrate for use in summer.

Removes fat, dirt from roads, insects etc. from the front screen.

Suitable for fan nozzle and headlights.

Gentle to rubber, plastic and varnish.

Lemon scented.



Summer window cleaner is available in the following container sizes:

container	part no.
11 bottle	X991 601 500 321
25l canister	X991 601 500 322



Vehicle and cabin care

Organic shine shampoo

Concentrated shampoo for vehicles with glossy effect and fresh smell.

Suitable for interior and exterior cleaning. Application: Mix with water 1 : 25 - 1 : 50 depending on scale of soiling. Biodegradable.



Organic shine shampoo is available in the following container sizes:

container	part no.
1l bottle	X991 601 500 532
10l canister	X991 601 500 531

Organic interior cleaner

Disinfectant universal cleaner with high cleaning power.

Removes oil, fat, wax, nicotine etc. easily. Application: Interior cleaner for tractor cabins, seats, ceiling trim, interior padding, plastic parts, ventilation ducts etc.

Mix concentrate with water: 1:5.



Organic interior cleaner is available in the following container sizes:

container	part no.
1I spray bottle	X991 601 500 512
10l canister	X991 601 500 511
25l canister	X991 601 500 513

The 11-spray bottle contains a ready mix and is refillable!

Interior foam cleaner

For the interior cleaning of soiled cabs.

Suitable for glass, screen surfaces, seats, ceiling, plastic parts. Use a microfibre cloth to wipe off. Dries without a trace.

Lemon scented.



Interior foam cleaner is available in the following container sizes:

9	
container	part no.

12x500ml can

X991 601 500 560

Cockpitfresh exclusive care

One product for several applications.

Ideal for leather care, plastic, car bumpers, garnish moulding, cleaning and sealing of motor and rubber parts and waterproofing of cabriolet roofs.



Cockpitfresh exclusive care is available in the following container sizes:

container	part no.
600ml can	X991 601 500 540

Vehicle and cabin care

Professional glass cleaner red

Ideal for both interior and external vehicle windows.

Immediate clear view, no irritating light reflections in the dark or when it rains. Removes silicone, fat, insects, nicotine etc. easily.

Application: Apply with spray nozzle, soak briefly and remove disolved dirt with a lint-free cloth or absorbent paper towel.



Professional glass cleaner red is available in the following container sizes:

container	part no.
1I spray bottle	X991 601 500 572
10l canister	X991 601 500 571

The 11-spray bottle is refillable!

Rubber/plastic balm

Cares, protects and maintains rubber elasticity.

To refresh rubber door seals and plastic parts.

Application: Apply on clean and dry rubber and plastic parts or wheels and spread with a sponge or cloth.



Rubber/plastic balm is available in the following container sizes:

container	part no.
1I spray bottle	X991 601 500 552*
10l canister	X991 601 500 551

The 11-spray bottle is refillable!

Rust film remover

Phosphorous foam cleaner for gentle and effective cleaning of rust film on varnished and chrome surfaces.

Suitable to also remove chalk and dirt in wash bays or to clean wheel rims and other vehicle parts.



Rust film remover is available in the following container sizes:

container	container	part no.	
	et to	V001 C01 F00 0	

5kg canister X991 601 500 201

Tree resin remover

Quickly and thoroughly removes resin stains and other contamination in a forestry work environment. Can also be used to clean equipment such as saw blades/chain saws.

Gentle on plastic, varnish, metal. Biodegradability > 89%, 21 days.



Tree resin remover is available in the following container sizes:

container	part no.
11 spray bottle	X991 601 500 501
5l canister	X991 601 500 502

The 11-spray bottle is refillable!

Vehicle and cabin care

Titan universal cleaner

Multipurpose cleaner for the cleaning of agricultural and forestry vehicles and machinery, equipment, trucks, workshop floors.

Suitable for hot and cold water pressure washers. Let it soak for 2-3 min. Mixing ratio: up to 1:20 Not intended for use on chrome.



Titan universal cleaner is available in the following container sizes:

container	part no.
5l canister	X991 601 500 582
25l canister	X991 601 500 581

Hand brush orange, B 25 Plus und B 50 Plus (with handle)

Cleaning brush with handle (acid resistant), 25cm and 50cm long. Soft bristles for a gentle cleaning of varnished surfaces.



Hand brush is available in the following sizes:

D 05 Dl...

B 25 Plus	part no.
1 piece	X991 601 500 410
B 50 Plus	part no.

Cleaning brush orange B 25

Cleaning brush with good detergent adhesion, 25cm wide.

Soft bristles for a gentle cleaning of varnished surfaces.

Suitable for use with shine shampoo and cold cleaner.



Cleaning brush orange and telescopic handle is available in the following:

cleaning brush B 25 part no.

1 piece	X991 601 500 490
telescopic handle	part no.
1 piece	X991 601 500 480

Telescopic handle 300 cm

Corrosion wax

Corrosion wax LH-2

Synthetic long-term anti corrosion wax, also suitable for sea and tropical climates.

For the exterior conservation of agricultural and municipal vehicles, steel panels, spare parts, tools etc. Color: light yellow. Sprayable.

Protection film: grip-dry

Can be kept for up to 12 months if stored outside.

Mix well before use.



Corrosion wax LH-2 is available in the following container sizes:

container	part no.	
5l canister	X991 601 500 242	
30l canister	X991 601 500 241	

Corrosion wax transparent 4600

Transparent anti-corrosion wax for all surfaces.

Protects varnished and chromed metal parts. Chemical and salt-water resistant.

For the conservation of industrial machines, motor parts, boats, metal panels, winter service and agricultural vehicles.

Can be polished on glass. Suitable for aluminium. Thickness of coating: 5µm (very low consumption, approx. 3-4l/tractor).



Corrosion wax transparent 4600 is available in the following container sizes:

container	part no.
11 can with srew lid	X991 601 500 253
400ml aerosol	X991 601 500 254

Spray gun 2000 KD

For application of Corrosion Wax Transparent 4600 in 11 can with thread.

Pressure at use: 6-8 bar.



Spray gun 2000 KD is available in the following:

container	part no.
1 piece	X991 601 500 470

Wax and fat remover

Removes wax and fat residues.



Wax and fat remover is available in the following container sizes:

container	part no.
1l bottle	X991 601 500 333
5l canister	X991 601 500 334



Radiator antifreeze blue (concentrate) Radiator antifreeze ready mix blue

Free from amine, nitrite and phosphate with long-term effect.

Protects from corrosion (according to ASTM D 3306). Prevents from cavitation damage, protects from sediment in the cooling system, gentle on varnish, tubing and sealing material. Suitable for use in summer and winter. According to the British norm BS6580, suitable for AGCO Power and Perkins engines. See page 22 for convenient assessories.



Radiator antifreeze blue is available in the following container sizes:

container	part no.
5l canister	X991 601 020 000
20l canister	X991 601 021 000
60l barrel	X991 601 022 000
208l barrel	X991 601 023 000



Radiator antifreeze ready mix blue is available in the following container sizes:

container	part no.
5l canister	X991 601 500 353
20l canister	X991 601 500 351
208l barrel	X991 601 500 352

Radiator antifreeze green 48 extra (concentrate) Radiator antifreeze ready mix green extra

Free from amine, nitrite and phosphate with long-term effect.

Protects from corrosion (according to ASTM D 3306, ASTM D 4985). Prevents from cavitation damage, protects from sediment in the cooling system, gentle on varnish, tubing and sealing material. Suitable for use in summer and winter. Suitable for Deutz engines according to norm DQC CA-14.

May also be used for engines from AGCO Power, Mercedes, MTU and MAN.

See page 22 for convenient assessories.



Radiator antifreeze green extra is available in the following container sizes:

container	part no.
5l canister	X991 601 005 000
20l canister	X991 601 006 000
60l barrel	X991 601 007 000
208l barrel	X991 601 008 000



Radiator antifreeze ready mix green extra is available in the following container sizes:

container	part no.
5l canister	X991 601 500 363
20l canister	X991 601 500 362
208l barrel	X991 601 500 361

Mixing table for the concentrates: Radiator antifreeze blue, Radiator antifreeze green 48 extra

concentrate	distilled water	protection
1 part	2 parts	-20° C
1 part	1,5 parts	-27° C
1 part	1 part	-37° C

Radiator antifreeze red-violet (concentrate)

AGCO Parts radiator antifreeze RED-VIOLET (G40, G12 ++) is a nitrite-, amine- and phosphate-free coolant based on ethylene glycol (ethanediol; monoethylene glycol) with Si-OAT technology.

Product characteristics:

AGCO radiator antifreeze RED-VIOLET (G40, G12 ++) provides excellent protection for all modern engines, especially heavily stressed aluminum engines, against frost, rust and overheating. It effectively prevents corrosion and deposits in the cooling system with its important components such as cooling channels in the cylinder head, engine block, radiator and water pump. Violet liquid.

AGCO radiator antifreeze RED-VIOLET (G40, G12 ++) is a special antifreeze concentrate and must be used with at least 33% vol. High heat transfer capacity.

Note:

Since the special application advantages of AGCO radiator antifreeze RED-VIOLET (G40, G12 ++) only arise when using solely radiator protection RED-VIOLET (G40, G12 ++), mixing with other radiator protection agents is not recommended.



Available in the following container sizes:

container	part no.
5l canister	X991 601 065 000
20l canister	X991 601 066 000
60l barrel	X991 601 067 000
208l barrel	X991 601 068 000

AGCO radiator antifreeze RED-VIOLET (G40, G12 ++) should be mixed with distilled water before filling into the cooling circuit and used in a concentration of 33 to 50 vol%.

Specifications:

From 2008 Audi, Bentley, Bugatti, Lamborghini, Seat, Skoda, VW TL 774 G, G12 Plus/Plus, Scania 1451, MB 325.5, MAN Si-OAT-System 324, Steyr MAT 3624, Deutz DQC CC-14. Particularly suitable for classic cars.

Antifreeze mixture table on page 15.



Radiator antifreeze orange (concentrate)

This frost protection is used in Valtra tractors from chassis number YK5N103H0FS086009 and in all Massey Ferguson tractors manufactured in Beauvais from chassis number H01601. The blue radiator antifreeze is used for machines before this serial number. It is not possible to mix these two antifreeze agents. Radiator protection Ready Mix Orange is a nitrite-, amine-, borate-, phosphate- and silicate-free additive for the radiator. Protects the cooler from frost, corrosion and increases the boiling point of the water. Suitable for aluminum motors. Improved heat transfer.

Product features:

- Protection against corrosion, cavitation and deposits.
- · Foam reduction.
- Environmentally friendly thanks to a longer service life.
- · Do not use with galvanized lines or containers.
- Organic acid technologie.
- Patented organic anti-corrosion inhibitors. (without silicate)

Application:

Radiator protection ORANGE contains high-quality corrosion protection additives and is characterized by o ptimal corrosion protection for all metals and metal alloys including aluminum used in the cooling system. (It can be used in cooling systems with fully aluminum motors, also as a life fill). Do not mix radiator antifreeze orange with other antifreeze!

Note:

Mix the radiator antifreeze with distilled water! According to the regulations of the engine manufacturers, the use concentration in the cooling system should be 50. This corresponds to ASTM D 3306. After filling, let the engine warm up with the heating switched on.



Available in the following container sizes:

container	part no.
5l canister	X991 601 055 000
20l canister	X991 601 056 000
60l barrel	X991 601 057 000
208l barrel	X991 601 058 000

Specifications:

ASTM D4985, AN 324 SNF, MB-approval 325.3, MTU MTL 5048, Porsche Carrera, Boxster, Cayenne, VW TL 774 D/F (Audi, Seat, Skoda, VW G12 Plus), Opel/GM 6277M, Ford WSS-M 97B44-D, Scania TI 02, CAT-construction machinery, VOLVO Coolant VCS, Renault VI, Perkins-engine from 2012, DAF-Coolant.

Antifreeze mixture table on page 15.

Radiator antifreeze ready mix orange

This frost protection is used in Valtra tractors from chassis number YK5N103H0FS086009 and in all Massey Ferguson tractors manufactured in Beauvais from chassis number H01601. The blue radiator antifreeze is used for machines before this serial number. It is not possible to mix these two antifreeze agents. Radiator protection Ready Mix Orange is a nitrite-, amine-, borate-, phosphate- and silicate-free additive for the radiator. Protects the cooler from frost, corrosion and increases the boiling point of the water.

Suitable for aluminum motors. Improved heat transfer.

For product properties, application, information and specifications see radiator antifreeze ORANGE.



Available in the following container sizes:

container	part no.
5l canister	X991 601 800 372
20l canister	X991 601 800 371
208l barrel	X991 601 800 373

Antifreeze mixture table on page 15.

Radiator antifreeze PINK (concentrate)

AGCO Parts radiator antifreeze PINK (G12+) is a nitrite-, amine-, borate-, phosphate- and silicate-free additive for the radiator.

Protects the cooler from frost, corrosion and increases the boiling point of the water.

Suitable for aluminum motors. Improved heat transfer and high chemical stability.

Product features:

- Protection against corrosion, cavitation and deposits.
- Foam reduction.
- Environmentally friendly thanks to a longer service life.
- · Do not use with galvanized lines or containers.
- OAT-technology.
- Patented organic anti-corrosion inhibitors. (without silicate)

Note:

Mix the radiator antifreeze with distilled water!

AGCO Parts radiator antifreeze PINK (G12 +) contains high-quality corrosion additives and is characterized by optimal corrosion protection for all metals and metal alloys including aluminum used in the cooling system. Do not mix AGCO radiator antifreeze PINK with other antifreeze agents!



Available in the following container sizes:

container	part no.
5l canister	X991 601 050 000
20l canister	X991 601 051 000
60l barrel	X991 601 052 000
208l barrel	X991 601 053 000

Specifications:

MAN 324 SNF, MB-approval 325.3, MTU MTL 5048, Porsche Carrera, Boxster, Cayenne, VW TL 774 D/F (Audi, Seat, Skoda, VW G12 Plus), Opel/GM 6277M, Ford WSS-M 97B44-D, Scania TI 02, CAT-construction machinery, Volvo Coolant VCS, Renault Vi.

Antifreeze mixture table see below.

Mixing table for all radiator antifreeze concentrates:

conzentrate	distilled water	antifreeze protection
1 part	2 parts	-20° C
1 part	1,5 parts	-27° C
1 part	1 part	-37° C

Mixing table for all radiator antifreeze ready mixtures:

ready mix	distilled water	antifreeze protection
pure		-40° C
1 part	1 part	-20° C

Brake antifreeze

Reliable antifreeze for pressurised air-braking systems.

Protects from frost down to -80°C, suitable for all manufacturers.



Available in the following container sizes:

container	part no.
1l bottle	X991 601 800 160

Fuel-Additive

Antiparaffin – flow improver

Additive to improve flow of diesel fuel.

Keeps injection nozzle clean, lowers engine sound, reduces fuel consumption and protects from corrosion. Clean combustion.
For vehicles with diesel particle filters,
Common Rail diesel or pump-injection.
Use with diesel fuel according to EN 590 or C.A.R.E..
Mixing ratio: 1:1000



Available in the following container sizes:

container	part no.
1I can	X991 601 800 101
5l canister	X991 601 800 103
20l canister	X991 601 800 102

Gasoline system cleaner

Gasoline system cleaner is a performance improving additive for gasoline/petrol,

which improves fuel efficiency and cleans the injection system and spark plugs.
Suitable for all gasoline vehicles with KAT, hybrid cars and vintage cars.
Use with gasoline fuel according to DIN EN 228 (ROZ 91, 95, 98, 100).



Available in the following container sizes:

container	part no.
250ml bottle	X991 601 800 112
1l can	X991 601 800 111

DPF cleaner diesel energy

High quality diesel-particle-filter-cleaner-additve.

Optimises the regeneration of DPF-filters and of the exhaust system, cleans the injection system. For all diesel vehicles and stationary engines with AdBlue, pump injection, Common Rail and aspirated diesel engine.

Effective against fungi and bacteria.
Use with diesel fuel according to EN 590 or C.A.R.E..
Reduced fuel consumption (up to 5%).
Patented product.



Available in the following container sizes:

container	part no.
250ml bottle	X991 601 800 126
1l can	X991 601 800 121
5l canister	X991 601 800 124
20l canister	X991 601 800 122
60l barrel	X991 601 800 125
208l barrel	X991 601 800 123

Turbo diesel injector cleaner

Diesel additive is a system cleaner suitable for off-highway and on-highway applications, which cleans and protects the fuel system.

Increases fuel efficiency in the combustion chamber and improves fuel economy and engine performance. Also effective against fungi and bacteria infestation. Suitable for vehicles with KAT, DPF, Common Rail and pump injection. Improves flow when winter diesel is used. Use with every tank, fuel consumption can be



Available in the following container sizes:

container	part no.
250ml bottle	X991 601 800 156
1l can	X991 601 800 151
5l canister	X991 601 800 154
20l canister	X991 601 800 152
60l barrel	X991 601 800 155
208l barrel	X991 601 800 153

reduced by max. 5%. Use with diesel fuel according to EN 590 or C.A.R.E..

System-Additive

Oil mud rinse

Removes combustion residues, oil-mud and harmful deposits inside the engine.

Reduces exhaust emission and improves emission values. Suitable also for vehicles with catalyser and vintage vehicles.

Attention: only use with low engine load. 300ml-can sufficient for 5-7l engine oil.



Available in the following container sizes:

container part no.

300ml can X991 601 800 130

OIL-STOP

OIL-STOP reduces consumption of engine oil and reactivates gasket materials. Lowers sound level of valve tappet and makes seals elastic again.

Fully effective after longer use.
Attention: Do not overdose!
300ml-can sufficient for 4-5l engine or transmission oil.



Available in the following container sizes:

container part no.

300ml can X991 601 800 140

Radiator cleaner

Flushing additive used in cooling systems for the removal of rust traces, limescale and mud in the radiator and coolant system.

Instructions for use: Mix the additive with clean water, or add directly to the antifreeze compartment. Start the engine and allow to circulate for 15 - 30 minutes. Empty the cooling system and rinse the system with clean water. Suitable for metals incl. aluminium. Gentle to rubber and gasket materials.



Available in the following container sizes:

container part no.

250ml bottle X991 601 800 260

Lubricants

Organic chain oil VG 100

Professional chain oil for traction chains and slide rails, i.e. of balers and field choppers.

Plant oil based with adhesive additive.
Wear and corrosion protective, high viscosity,

Wear and corrosion protective, high viscosity protects from tree resin.

All year use for chain saws of DOLMAR, SOLO, Jonsered, Makita, Husquvarna, STIHL.



Available in the following container sizes:

container	part no.
5l canister	X991 601 800 183
20l canister	X991 601 800 181
60l barrel	X991 601 800 184
208l barrel	X991 601 800 182

Chain oil EP-100 mineral

Special adhesive lubricant for drive chains and slide rails, typical applications include balers, mowers and forage / combine harvesters.

Extreme pressure applications.

Also suitable for chain saws.



Available in the following container sizes:

container	part no.
5l canister	X991 601 800 223
20l canister	X991 601 800 221
60l barrel	X991 601 800 224
208l barrel	X991 601 800 222

CA Grease 5000 Synthetic adhesive grease spray

Synthetical, extremely adhesive high performancegrease spray.

Corrosion and wear protective. Salt-water resistant and emulsion persistant. For use in agriculture and forestry, construction and metal industry as well as vehicle workshops. For open ropes, rolls, coupling, joints, chains, Bowden cables etc.

Yellow-fluorescent.

Application temperature: -30°C up to +110°C



Available in the following container sizes:

container	part no.
500ml can	X991 601 800 190

CA-Plex S 2 Adhesive fat neon

Water resistant long term grease with synthetic oil component and exceptional adhesive characteristics.

For industry, agricultural and forestry machines and vehicles.

KP 2 G-30

Application temperature: -30°C up to +110°C

NLGI: 2, CA12 0H

Suitable grease gun on page 22.



Available in the following container sizes:

container part no.

	•
400g cartridge	X991 601 800 590

Lubricants

White PTFE grease

Builds up a water- and saltwater resistant film with high mechanical load.

Corrosion protective. Against squeaking of bolts, hinges, rails, switching mechanisms, rolls, gears, open ball bearings.

Suitable as battery terminal grease.

Application temperature: -35°C up to +110°C



Available in the following container sizes:

container part no.

400ml can X991 601 800 340

Multifunctional oil 6000

Lubrifies mechanics, against squeaking, penetrates rust, displaces humidity.

Greases hinges, rolls, bolts, pneumatic tools. Disolves rust and untightens seized up parts. Professional use in industry, craft and workshops. Also as contact spray indispensible.



Available in the following container sizes:

container part no.

 400ml can
 X991 601 800 281

 5l can
 X991 601 800 282

Professional rust remover MOS 2

Multipurpose professional lubrifying and greasing antiseize agent with high creep strength.

Displaces humidity, untightens seized up screws, bolts and nuts.

Removes rust and protects from corrosion.

Can be used as contact spray.



Available in the following container sizes:

container part no.

400ml can X991 601 800 300

Detention chain spray

High quality adhesive chain spray builts up long term lubrication film.

Resistant against saltwater, acids and lyes and oxidation. Effective against rust, reduces wear and inhibits noise.

Application temperature: -30°C up to +210°C



Available in the following container sizes:

container part no.

400ml can X991 601 800 210

Cleaners for workshop and vehicles

Engine cleaner

Fat and oil removing engine cleaner with re-greasing effect.

Sticks even to vertical surfaces due to its highly viscous consistence. Effective cleaning. Cleaned engine parts can immediately be treated further.

Application: Spray on engine parts and wipe off after 15 min. of soaking. Rinse thourougly afterwards. Gentle to varnish, aluminium and rubber parts. Attention: Do not use on hot surfaces!



Available in the following container sizes:

container	part no.
500ml can	X991 601 800 270

Small parts cleaner

Special cleaner for the cleansing of small parts.

Easily applied by brushing or dipping.
Free of chlorinated solvents (odor free).
Do not mix with water!



Available in the following container sizes:

container	part no.
20l canister	X991 601 800 231
60l barrel	X991 601 800 233
200l barrel	X991 601 800 232

Oil binder fine grain

Binder for oil and chemicals.

Dust-free. Exceptionally absorbent and slip resistant.
Granulation 0.5-1mm, typ III/R,

according to LTws-No. 27. Especially suitable for soaking up harmful oil residues in workshops or streets, on concrete or asphalt.

pH-value: 6.9



Available in the following container sizes:

container	part no.
10kg sack	X991 601 800 291
15kg bucket (for disposal)	X991 601 800 292
20kg sack	X991 601 800 293

LHM Fluid+

Special hydraulic-fluid for level regulation.



Available in the following container sizes:

container	part no.
1l can	X991 601 800 170

Maintenance products

Gear grease EP 00/000

For lubrication of rolling-, ball- and slide bearings.

For use in the central lubrication unit with pipes, for high pressure loads i.e. in agricultural- and

construction vehicles.

trucks and industrial installations.

Application temperature:

-50°C to +120°C,

short term up to +140°C.



Gear grease EP 00/000 is available in the following container sizes:

container	part no.
900g tube	X991 601 500 601
25kg tin	X991 601 500 602
50kg tin	X991 601 500 603

Longterm grease B2

Water resistant, EP-lithium complex soap greases for high thermal and mechanical loads of rolling, ball and slide bearings.

High temperature lubricant.

Especially for wheel hubs and release bearings.

Color: blue

Application temperature: -35°C up to +150°C

NLGI 2, KP2N-35, DIN 51502

Suitable accessories see page 22 (manual lever grease gun).



Longterm grease B2 is available in the following container sizes:

container	part no.
400g cartridge	X991 601 500 621
25kg tin	X991 601 500 622
50kg tin	X991 601 500 623

High temperature paste with PTFE

Synthetic anti-seize paste with PTFE.

Builds up a strong and lasting film and prevents metal-on-metal contact.

For agricultural and construction vehicles, trucks, machine mounting. Suitable for use on brass, steel, galvanised steel, aluminium, copper, PVC and glass fibre. Chemical resistant.

Application temperature: -30°C up to +140°C



High temperature paste is available in the following container sizes:

container	part no.
510g can with brush	X991 601 500 610

Assessory equipment

Manual drum pump with tube

Drum pump with tube for 200l or 60l barrel.

Suitable for oil and diesel.

For use with baler gear oil CLP ISO 150 and baling chain oil CGLP 100.



Manual drum pump is available:

container part no.

1 piece X991 601 500 430

Manual lever grease gun "Profiline"

Grease gun for 400g catridges (DIN 1284-standard).

1.9 cm³/pass, Twin-Lock system, variable adjustment of plunger rod, 1000bar-tube, 30cm long, M10x1, venting valve.



Manual lever grease gun "Profiline" is available:

container part no.

1 piece X991 601 500 440


For use with lonterm grease B2.

Manual lever plunger pump universal AF 10

One pump for multiple uses.

Diesel, heating oil, lubricants (up to max. 150mm²/s), anti-freeze etc.. Polypropylene. For 60l to 200l-barrels, approx. 0.25l/pass..

For use with baler gear oil CLP ISO 150, baling chain oil CGLP 100 and antifreeze products.



1 piece X991 601 500 450

Drain tabs



X991 601 800 391



X991 601 800 392



X991 601 800 393

Drain tabs are available:

drain tab	for container	part no
1 piece	10l/kg canister	X991 601 800 391
1 piece	25l/kg canister	X991 601 800 392
1 piece ¾"	60l/208l barrel	X991 601 800 393

Spraying equipment

Pressure sprayer CleanMaster CM 80

81 volume.

Pressure sprayer with carry strap suitable for acid or lye cleaning products with a pH-value between 2 and 12. Working pressure 3 bar. Clear container with strong pump, plastic spray lance (incl. 0.5m-extension pipe) with acid-proof flat-jet nozzle. Ideal for car-washing and use in workshops.



Available as follows:

container part no.
1 piece X991 601 800 401

Pump dispenser CleanMaster EX 100

11 volume.

Special pump dispenser for disolvent containing means, i.e. rim cleaner, brake cleaner and oil. Suitable for cleaners with pH-values between 5 and 10. Working pressure 3 bar. Continuously adjustable hollow cone spray nozzle. Clear container with strong pump. For use in workshops, service stations, agriculture etc.



Available as follows:

container part no.
1 piece X991 601 800 402

Pump dispenser

11 volume.

Reusable plastic pump dispenser for chemical cleaners, i.e. windown cleaner, water, bathroom cleaner, cold cleaners etc.



Available as follows:

container part no.

1 piece X991 601 800 460

Skincare

AGRI CLEAN Hand cleaner

Highly effective, viscous hand cleaner for daily use in workshops and on the farm.

Contains moisturising components which sooth the skin and protect it from dying out. AGRI CLEAN is especially suitable to remove persistant dirt and smells. Natural orange oil gives AGRI CLEAN a pleasant fresh fragrance. Apply on wet hands and rinse with plenty of water.



The 50g/50ml bottles are ideal to promote the skincare products and convince your customers!

Hand cleaner is available in the following container sizes:

container	part no.
50g bottle	X991 502 014 000
500g bottle	X991 502 005 000
2kg softbottle	X991 502 013 000*
5kg canister	X991 502 006 000

AGRI CARE Hand cream with olive oil

Fast absorbing hand cream with olive oil.

Protects and moisturises skin.



Hand cream is available in the following container sizes:

container	part no.
50ml bottle	X991 502 016 000
500ml bottle	X991 502 007 000
2l softbottle	X991 502 015 000
5l canister	X991 502 008 000

AGRI PROTECT Skin protection gel

Works like an invisible glove and protects from acids and aggressive substances, such as brake dust and soot.

Apply and rub into hands prior to work.



Skin protection gel is available in the following container sizes:

container	part no.
500ml bottle	X991 502 009 000
2l softbottle	X991 502 017 000
5l canister	X991 502 010 000

AGRI SEPT Disinfecting gel

Ready-to-use hygienic hand disinfectant gel. Moisturising.

Rub hands thoroughly with the product and keep them moist for between 30 to max. 60 seconds.



Disinfecting gel is available in the following container sizes:

container	part no.
50ml bottle	X991 502 020 000
11 hottle	X991 502 019 000

Skincare

Dosing pump for 5l-canister



Dosing pump is available:

container part no.
1 piece X991 502 011 000

Dispenser for 2I-softbottle





Dispenser for 21-softbottle is available:

container part no.

1 piece X991 502 018 000

Wall bracket for 5l-canister



Wall bracket for 51-canister is available:

container part no.

1 piece X991 502 012 000

Animal house hygiene

Acidic livestock building cleaner LM

Liquid concentrate.

For the intensive cleaning of stables and slaughter rooms, milking parlours as well as press houses and all floors and equipment in the food processing and food production industry.

Removes rust, chalk and urine residues.



Acidic livestock building cleaner is available in the following container sizes:

container	part no.
5l canister	X991 502 023 000
20l canister	X991 502 022 000

Alkaline livestock building cleaner LM

Liquid concentrate.

For the intensive cleaning of stables and slaughter rooms, milking parlours as well as press houses and all floors and equipment in the food processing and food production industry.

Removes persistant soiling like faeces, blood, protein and grease.



Alkaline livestock building cleaner is available in the following container sizes:

container	part no.
5l canister	X991 502 025 000
20l canister	X991 502 024 000

General livestock building cleaner

Liquid concentrate.

For the professional cleaning of livestock stables. Removes organic fats easily.



General livestock building cleaner is available in the following container sizes:

container	part no.
5l canister	X991 502 027 000
20l canister	X991 502 026 000

Organic surface disinfectant

Highly effective surface disinfectant cleaner.

For toilets, shower systems, smooth ceramic surfaces, upholstery fabrics, vehicle parts, plastic and wooden surfaces. This organic product is gentle on the skin and is pleasant to work with. Removes bacteria and fungi, whilst also rendering viruses and germs harmless. Safe for humans, animals and the environment.



Organic surface disinfectant is available in the following container sizes:

container	part no.
5l canister	X991 601 800 600
25l canister	X991 601 800 601
208l barrel	X991 601 800 602

notes	

