

FENDT VARIABLE ROUND BALERS

Equipment variants and technical details.

		4160 V	4160 V Xtra	4180 V	4180 V Xtra
General data					
Baler chamber diameter	m	0,70 - 1,60	0,70 - 1,60	0,70 - 1,80	0,70 - 1,80
Baler chamber width	m	1,23	1,23	1,23	1,23
Baler chamber volume	m ³	2,50	2,50	3,10	3,10
Infinite belt	Number	4	4	4	4
Overall height	m	3,05	3,05	3,25	3,25
Overall length	m	5,00	5,00	5,10	5,10
Overall width	m	2,70	2,70	2,70	2,70
Approx. weight	kg	3.950	3.950	4.200	4.200
Power requirement	kW/hp	55 / 80	55 / 80	70 / 110	70 / 110
Drive/gearbox					
Power Split gearbox		■	■	■	■
PTO drive	rpm	540	540	540	540
Automatic chain lubrication		■	■	■	■
Lifetime lubricated roller bearings		■	■	■	■
Bearing lubricated by lubricating points on both sides			■		■
Automatic roller lubrication					
Drawbar					
Height-adjustable traction drawbar		■	■	■	■
Rigid drawbar eye hitch		□	□	□	□
Turnable drawbar eye hitch		■	■	■	■
K80 hitch		□	□	□	□
Pick-Up					
Uncontrolled pick-up		■	■	■	■
Pick-up 2.00 m		□	□	□	■
Pick-up 2.25 m		■	■	■	□
Pick-up 2.40 m			□		□
Tine rows	Number	5	5	5	5
Tine spacing	mm	64	64	64	64
Baffle plate		■		■	
Roller pressure pad		□	■	□	■
Rigid pick-up wheels		■	■	■	■
Swinging pick-up wheels		□	□	□	□
Alpine kit		□	□	□	□
Table/rotor					
Without table with conveyor rotor		■		■	
Without table – 2-star conveyor rotor		□		□	
XtraCut – 13 knives with 2-star conveyor rotor			■		■
XtraCut – 17 knives with 2-star conveyor rotor with group shift (8-9-17)			□		□
XtraCut – 25 knives with Profi rotor with group shift (12-13-25)			□		□
Potential cutting length	mm		90 / 70 / 45		90 / 70 / 45
Fixed conveyor floor		■		■	
HydroflexControl cutting floor			■		■

FENDT VARIABLE ROUND BALERS

Equipment variants and technical details.



		4160 V	4160 V Xtra	4180 V	4180 V Xtra
Tying					
Varionet net tie		■	■	■	■
Variotwin twine tie		□	□	□	□
Easy Load System ELS		■	■	■	■
Additional net roll holder		■	■	■	■
Additional twine box		□	□	□	□
Bale ejector		□	■	□	■
Bale shape indicator		□	□	□	□
Additional drive system (ADS)		■	□	■	■
Controls					
E-Link Control		■		■	
E-Link Pro		■	□	■	□
ISOBUS		□	■	□	■
Chassis					
Trailer axle		■	■	■	■
Hydraulic brake assembly			□		□
Compressed air brake assembly			□		□
Permitted top speed undamped	km/h	25	25	25	25
Permitted top speed damped	km/h	40	40	40	40
Tyres					
15/55-17		■	■	■	■
19/45-17		□	□	□	□
500/45-22,5			□		□
500/50-22,5			□		□
500/60-22,5			□		□
500/55-20			□		□