

# Technical Specifications.



		5275 C	5275 C PL	5275 C PLI	5275 C Rice	6335 C	6335 C PL	6335 PLI	6335 C Rice
<b>Table</b>									
Table widths FreeFlow from - to	m	4.80 - 7.60	4.80 - 7.60	4.80 - 7.60	4.80 - 7.60	4.80 - 7.60	4.80 - 7.60	4.80 - 7.60	4.80 - 7.60
Cutting frequency FreeFlow	cuts/min	1254	1254	1254	1254	1254	1254	1254	1254
Table widths PowerFlow from - to	m	5.50 - 6.80	5.50 - 6.80	5.50 - 6.20		5.50 - 7.70	5.50 - 6.80	5.50 - 6.20	
Cutting frequency PowerFlow	cuts/min	1220	1220	1220		1220	1220	1220	
TerraControl II™ table guidance		■	■	■	■	■	■	■	■
Rape auger		□	□			□	□		
Electric rape knife		□	□	□		□	□	□	
Multi-coupler		■	■	■	■	■	■	■	■

<b>Corn header</b>									
CornFlow™		□	□	■		□	□	□	
Rows (foldable)	number	6	6	6		6	6	6	
Rows (rigid)	number	6 - 8	6 - 8	6 - 8		6 - 8	6 - 8	6 - 8	
Row spacing	cm								
Stalk chopper		□	□	□		□	□	□	
Intake auger		■	■	■		■	■	■	

<b>Crop elevator</b>									
Power Feed Roller		■	■	■	■	■	■	■	■
Intake chains	number	3	3	3	3	4	4	4	4
Hydraulic reverse		■	■	■	■	■	■	■	■

<b>Threshing system</b>									
MCS Plus threshing unit		■	■	■	■	■	■	■	■
Threshing cylinder width	mm	1340	1340	1340	1340	1600	1600	1600	1600
Threshing cylinder diameter	mm	600	600	600	600	600	600	600	600
Threshing cylinder speed	rpm	380 - 1100	380 - 1100	380 - 1100	380 - 1100	430 - 1210	430 - 1210	430 - 1210	430 - 1210
Concave wrap	degrees	106.0	106.0	106.0	106.0	106.0	106.0	106.0	106.0
Concave area, total	m²	0.99	0.99	0.99	0.99	1.18	1.18	0.99	1.18
Concave bars	number	12	12	12	12	12	12	12	12
Sectional concave		□	□	□		□	□	□	
Maize equipment kit		□	□	□	□	□	□	□	□

<b>Residual grain separation</b>									
Multi Crop Separator Plus (MCS Plus)		■	■	■	■	■	■	■	■
Active total separation area	m²	1.89	1.89	1.89	1.89	2.25	2.25	2.25	2.25
Straw walkers	number	5	5	5	5	6	6	6	6
Steps	number	4	4	4	4	4	4	4	4
Straw walker length	mm	4256	4256	4256	4256	4256	4256	4256	4256
Straw walker area	m²	5.73	5.73	5.73	5.73	6.81	6.81	6.81	6.81
Total separation area	m²	7.62	7.62	7.62	7.62	9.06	9.06	9.06	9.06

<b>Cleaning</b>									
Sectional cleaning system		■	■	■	■	■	■	■	■
Preparation floor, in sections and detachable		■	■	■	■	■	■	■	■
Preparation floor area	m²	2.57	2.57	2.57	2.57	3.06	3.06	3.06	3.06
Total sieve area	m²	4.67	4.67	4.67	4.67	5.58	5.58	5.58	5.58
Fan speed	rpm	350 - 1050	350 - 1050	350 - 1050	350 - 1050	350 - 1050	350 - 1050	350 - 1050	350 - 1050
Blower speed, reduced	rpm	270 - 840	270 - 840	270 - 840	270 - 840	270 - 840	270 - 840	270 - 840	270 - 840
Electrical blower setting		■	■	■	■	■	■	■	■
HC sieves		■	■	■	■	■	■	■	■
Electric sieve adjustment		■	■	■	■	■	■	■	■
Returns indicator		■	■	■	■	■	■	■	■
Returns camera		□	□		□	□	□	□	□

<b>Grain tank</b>									
Grain tank capacity	litres	9000	8600	8600	9000	9000	8600	8600	9000
Turret unloading		■	■	■	■	■	■	■	■
Unloading rate	l/s	105	105	105	105	105	105	105	105
Unloading tube length	m	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Flap and slide for taking samples		■	■	■	■	■	■	■	■

		5275 C	5275 C PL	5275 C PLI	5275 C Rice	6335 C	6335 C PL	6335 PLI	6335 C Rice
<b>Straw chopper</b>									
Straw chopper		■	■	■	■	■	■	■	■
72 serrated knives		■	■	■	■				
88 serrated knives						■	■	■	■
Chaff spreader		□	□	□	□	□	□	□	□
Electrically adjustable deflector plates		□	□	□	□	□	□	□	□
Quick-switch (chopping/swathing)		■	■	■	■	■	■	■	■

<b>Engine</b>									
AGCO Power Engine		■	■	■	■	■	■	■	■
Tier4final / Stage 4 emissions		■	■	■	■	■	■	■	■
Cylinders	number	6	6	6	6	6	6	6	6
Displacement	litres	7.4	7.4	7.4	7.4	8.4	8.4	8.4	8.4
Max. performance with PowerBoost (ECE R 120)	kW/hp	225/306	225 / 306	225 / 306	225 / 306	265 / 360	265 / 360	265 / 360	265 / 360
Fuel tank capacity	litres	620	620	620	620	620	620	620	620
AdBlue tank capacity	litres	80	80	80	80	80	80	80	80

<b>Chassis</b>									
Hydrostatic drive		■	■	■	■	■	■	■	■
Gear steps	number	4	4	4	4	4	4	4	4
Mechanical gear shift		■	■	■	■	■	■	■	■
Four-wheel drive		□	□	■		■	□	■	
Atrak crawler track						□			
ParaLevel slope compensation			■	■			■	■	
ParaLevel Integrale slope compensation				■				■	
ParaLevel slope compensation, four-wheel drive	degrees		20.0	20.0			20.0	20.0	
ParaLevel slope compensation, front-wheel drive	degrees		15.0				15.0		

<b>Cab</b>									
Skyline cab		■	■	■	■	■	■	■	■
Air-suspended driver seat		■	■	■	■	■	■	■	■
Automatic climate control		■	■	■	■	■	■	■	■
Heating		■	■	■	■	■	■	■	■
Electrically adjustable heated exterior mirrors		■	■	■	■	■	■	■	■
Additional wide-angle mirror		■	■	■	■	■	■	■	■
Additional work light		□	□	□	□	□	□	□	□
Radio		□	□	□	□	□	□	□	□
Reversing camera		■	■	■	■	■	■	■	■
Cooler compartment integrated into the passenger seat		□	□	□	□	□	■	□	□
Headlamps		□	□	□	□	□	□	□	□
Loss indicator		■	■	■	■	■	■	■	■

<b>Fendt Variotronic</b>									
Fendt Varioterminal 10.4"		■	■	■	■	■	■	■	■
Fendt VarioGuide		□			□	□			□
AgCommand™		■	■	■	■	■	■	■	■
Yield and moisture measurement		□	□	□	□	□	□	□	□
Yield mapping		□	□	□	□	□	□	□	□

<b>Weights and dimensions</b>									
Length without table	m	9.04	9.0	9.0	9.04	9.04	9.0	9.0	9.04
Width without table, standard tyres	m	3.65	3.55	3.55		3.9	3.82	3.87	
Weight base machine, without table, without optional equipment	kg	13500	14800	15200		14000	15300	15700	
Height	m	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0

<b>Tyres</b>									
Drive axle tyres (standard)		800/65R32	800/65R32	800/65R32		800/65R32	800/65R32	800/65R32	
Steering axle tyres (standard)		460/70R24	540/65R24	540/65R24		460/70R24	540/65R24	540/65R24	
<b>Transport widths</b>									
Atrak crawler track (24" - 610 mm)	mm					3490			
800/65R32	mm	3490	3490	3490	3490		3770		
800/65R32	mm	3645	3550	3550	3645		3900	3823	3870
710/75R32	mm	3400	3400	3400	3400		3700	3683	3700
650/75R32	mm	3280	3290	3315	3280		3485	3498	3485

\* = depends on country - additional legal constraints may apply