

Standard and optional equipment
 Standard: ■
 Optional: □

FENDT ROTANA V COMBI

Equipment variants and technical details.



		Rotana 160 V	Rotana 160 V Xtra	Rotana 180 V	Rotana 180 V Xtra	Rotana 160 V Combi
Drive/gearbox						
Power Split gearbox		■	■	■	■	■
PTO drive	rpm	540	540	540	540	540/1000
Automatic chain lubrication		■	■	■	■	■
Lifetime lubricated roller bearings		■		■		
Bearing lubricated by lubricating points on both sides			■		■	■
Drawbar						
Height-adjustable traction drawbar		■	■	■	■	■
Rigid drawbar eye hitch		■	■	■	■	■
Turnable drawbar eye hitch		□	□	□	□	□
K80 hitch		□	□	□	□	□
Pick-Up						
Uncontrolled pick-up		■	■	■	■	■
Pick-up 2.25 m		■	■	■	■	■
Pick-up 2.40 m			□		□	□
Tine rows	Number	5	5	5	5	5
Tine spacing	mm	64	64	64	64	64
Baffle plate		□		□		
Fixed roller windguard		□	□	□	□	
Variable roller windguard		■	■	■	■	■
Rigid pick-up wheels		■	■	■	■	■
Swinging pick-up wheels		□	□	□	□	■
Alpine kit		□	□	□	□	□
Table/rotor						
Without table with conveyor rotor		■	□	■	□	
XtraCut – 13 knives with 2-star conveyor rotor			■		■	□
XtraCut – 17 knives with 2-star conveyor rotor with group shift (8-9-17)			□		□	□
XtraCut – 25 knives with Profi rotor with group shift (12-13-25)			□		□	□
Additional set of knives						□
Potential cutting length	mm		90 / 70 / 45		90 / 70 / 45	90 / 70 / 45
Fixed conveyer floor		■		■		
HydroflexControl cutting floor			■		■	■
Tying						
VarioNet net tie		■	■	■	■	■
Easy Load System ELS		■	■	■	■	■
Additional net roll holder		□	■	□	■	
Bale ejector		□	■	□	■	
Bale shape indicator						□
Additional drive system (ADS)		■	■	■	■	
Equipment at startup			□		□	□
Controls						
E-Link Control		■	■	■	■	
E-Link Pro			□		□	□
ISOBUS			□		□	■
Chassis						
Trailer axle		■	■	■	■	■
Hydraulic brake assembly		□	□	□	□	□
Compressed air brake assembly		□	□	□	□	□
Permitted top speed undamped	km/h	25	25	25	25	25
Permitted top speed damped	km/h	40	40	40	40	40

Wrapping unit

		Rotana 160 V	Rotana 160 V Xtra	Rotana 180 V	Rotana 180 V Xtra	Rotana 160 V Combi
Foil width 500 mm						□
Foil width 750 mm						□
Foil capacity	Number					12+2
Pre-stretch 33%/55%/70%						■
Foil tear monitoring						■
3 work lights						□
2 colour cameras						□
Front bale chute						□
Additional film pressure						□

Tyres

		Rotana 160 V	Rotana 160 V Xtra	Rotana 180 V	Rotana 180 V Xtra	Rotana 160 V Combi
15/55-17		■	■	■	■	
19/45-17		□	□	□	□	
480/45-17		□	□	□	□	
500/45-22,5		□	□	□	□	
500/50-22,5			□		□	
500/60-22,5 V-Profile Flotation			□		□	
500/55-20		□	□	□	□	
600/55 R26,5 V-Profile Flotation						□
620/55 R26,5						■

General data

		Rotana 160 V	Rotana 160 V Xtra	Rotana 180 V	Rotana 180 V Xtra	Rotana 160 V Combi
Baler chamber diameter	m	0,70 - 1,60	0,70 - 1,60	0,70 - 1,80	0,70 - 1,80	0,90 - 1,60
Baler chamber width	m	1,23	1,23	1,23	1,23	1,23
Baler chamber volume	m³	2,50	2,50	3,10	3,10	2,50
Infinite belt	Number	4	4	4	4	4
Overall height	m	3,05	3,05	3,25	3,25	3,15
Overall length	m	5,00	5,00	5,10	5,10	6,30
Overall width	m	2,70	2,70	2,70	2,70	2,90
Approx. weight	kg	3.950	3.950	4.200	4.200	6.550
Power requirement	kW/HP	55 / 80	55 / 80	70 / 110	70 / 110	100/140



FENDT ROLLECTOR

	Rollector 130	Rollector 160
Controls		
E-Link Basic	■	
Wrapping unit		
Bale wrapper	■	■
Without bale ejector	■	■
Bale twister	□	□
Bale ejector arm	□	■
Support plate discharge arm	□	
Speed adjustment kit	■	■
Work lights	■	■
Tyres		
10.0/75-15,3	■	
380/55-17		■

General data

		Rollector 130	Rollector 160
Overall height	m	2,30	2,70
Overall length	m	4,70	5,80
Overall width	m	2,55	2,30
Approx. weight	kg	1.080	2.110
Power requirement	kW/HP	30/40	40/55
Bale diameter	m	0,90 - 1,30	1,25-1,50
Bale width	m	1,25	1,25
Bale weight	kg	1.000	1.250