

Standard and optional equipment  
 Standard: ■  
 Optional: □

FENDT TIGO (ST/S)

# Equipment variants and technical details.



	Tigo 35 ST	Tigo 40 ST	Tigo 50 ST	Tigo 35 S	Tigo 40 S	Tigo 50 S
<b>Drawbar</b>						
Hydraulically-adjustable articulated drawbar	□	□	□	□	□	□
Rigid top hitch with drawbar eye	■	■	■	■	■	■
Bottom hitch with K80	□	□	□	□	□	□
Bottom hitch with rotating drawbar eye	□	□	□	□	□	□
<b>Pick-Up</b>						
Windguard	■	■	■	■	■	■
Self-steering PU feeler wheels	□	□	□	□	□	□
<b>Table/rotor</b>						
Silage table with 16 knives	□	□	□	□	□	□
Hydraulic table operation	□	□	□	□	□	□
<b>Loading space assembly</b>						
Acoustic fill level indicator	□	□	□	□	□	□
Side canvas	□	□	□	□	□	□
Hydraulically foldable dry forage assembly	□	□	□	□	□	□
Closed metal dry forage wagon	□	□	□	□	□	□
Tubular frame attachment for dry forage wagon	□	□	□	□	□	□
Hay module	□	□	□	□	□	□
<b>Chassis</b>						
Single axle mudguard	□	□	□	□	□	□
Tandem axle mudguard	□	□	□	□	□	□
<b>Operation</b>						
Comfort controls	■	■	■	■	■	■
<b>Tyres</b>						
380/55-17 Flotation +	■	■	■	■	■	■
480/45-17 Flotation +	□	□	□	□	□	□
500/50-17	□	□	□	□	□	□

\* = specific to the country

## Technical data

		Tigo 35 ST	Tigo 40 ST	Tigo 50 ST	Tigo 35 S	Tigo 40 S	Tigo 50 S
Volumes in accordance with DIN 11741	m³	22	24,5	29	22	24,5	29
Volumes with moderate compression	m³	34	37	47	34	37	47
Power requirement	kW/HP	29/40	44/60	51/70	29/40	44/60	51/70
Unladen weight	kg	2.700	3.280	3.580	2.790	3.550	3.850
Permissible overall weight*	kg	5.250	9.000	9.000	6.200	9.500/11.000	9.500/11.000
Overall width	m	2,40	2,40	2,40	2,40	2,40	2,40
Overall length	m	8,05	8,65	9,70	8,05	8,65	9,70
Overall height	m	2,00 / 3,05	2,05 / 3,05	2,05 / 3,05	2,25 / 3,25	2,45 / 3,40	2,45 / 3,40
Loading area width	m	1,65	1,65	1,65	1,65	1,65	1,65
Loading area length	m	4,85	5,45	6,15	4,85	5,45	6,15
Track width	m	2,12	2,12	2,12	1,80	1,80	1,80
Permissible drawbar load	kg	1.500	1.500	1.500	1.500	1.500	1.500
Pick-up tine bar	Number	5	5	5	5	5	5
Pick-up operating width in accordance with DIN	cm	180	180	180	180	180	180
Swinging pick-up		■	■	■	■	■	■
Tine spacing	mm	54	54	54	54	54	54
Pick-up ground clearance	cm	40-70	40-70	40-70	40-70	40-70	40-70
Conveyor swing arm		■	■	■	■	■	■
Conveyor swing arm	Number	5	5	5	5	5	5
Maximum number of knives	Number	33	33	33	33	33	33
Potential cutting length	mm	38	38	38	38	38	38
Maximum 25 km/h		□	□	□	□	□	□
Maximum 40 km/h		□	□	□	□	□	□
Single axle		■	■	■	■	■	■
Leaf spring tandem chassis		■	■	■	■	■	■
Hydraulic braking system		□	□	□	□	□	□
Hydraulic safety brake		□	□	□	□	□	□
Compressed air brake system		■	■	■	■	■	■
Load-dependent braking system		■	■	■	■	■	■

\* = specific to the country

