

# Equipment variants.\*

Cargo T955	
<b>Engine</b>	
Reversible fan	<input type="checkbox"/>
Fuel pre-filter	<input checked="" type="checkbox"/>
Cyclone blower for air filters	<input type="checkbox"/>
Electrical engine pre-heating	<input type="checkbox"/>
<b>Transmission</b>	
Stepless drive 20 km/h	<input checked="" type="checkbox"/>
Stepless drive 30 km/h	<input type="checkbox"/>
Stepless drive 40 km/h	<input type="checkbox"/>
Loader, forklift and road mode	<input checked="" type="checkbox"/>
Slow-drive control	<input type="checkbox"/>
Acoustic signal when reversing	<input checked="" type="checkbox"/>
<b>Loading system</b>	
Overload system	<input checked="" type="checkbox"/>
Z-bar linkage	<input checked="" type="checkbox"/>
Boom absorption	<input type="checkbox"/>
Dirt wiper on telescope	<input type="checkbox"/>
Shake function	<input checked="" type="checkbox"/>
Automatic bucket reset	<input type="checkbox"/>
Tilt-cylinder lock	<input type="checkbox"/>
Sennebogen quick release, mechanical	<input checked="" type="checkbox"/>
Sennebogen quick release, hydraulic	<input type="checkbox"/>
Quick release compatible with Volvo implements, hydr.	<input type="checkbox"/>
Quick release compatible with JCB implements, hydr.	<input type="checkbox"/>
Quick release compatible with Manitou implements, hydr.	<input type="checkbox"/>
Quick-change device suitable for Kramer implements, hydr.	<input type="checkbox"/>
Weighing system	<input type="checkbox"/>
<b>Implements</b>	
Implement plate load capacity 4,990 kg	<input type="checkbox"/>
Implement plate load capacity 5,500 kg	<input type="checkbox"/>
Pallet fork, max. load capacity 5,500 kg, tine length 1,200 mm	<input type="checkbox"/>
Pallet fork, max. load capacity 5,500 kg, tine length 1500 mm	<input type="checkbox"/>
Tine adjustment with lateral shifter	<input type="checkbox"/>
1.6 m³ soil bucket with teeth for bulk densities of up to 1,800 kg/m³	<input type="checkbox"/>
3.0 m³ loading bucket for bulk densities of up to 1,100 kg/m³	<input type="checkbox"/>
4.0 m³ light-goods bucket including reversible blade. For bulk densities up to 900 kg/m³, 2.55 m wide	<input type="checkbox"/>
4.0 m³ light-goods bucket including turning blades for bulk densities up to 900 kg/m³, 2.80 m wide	<input type="checkbox"/>
Silage grab bucket 2.8 m³	<input type="checkbox"/>
Large bale forks – heavy-duty – width 2 m with 4 tines	<input type="checkbox"/>
Round and square baler tine	<input type="checkbox"/>
Rotary clamp fork	<input type="checkbox"/>
Big bag holder	<input type="checkbox"/>
Adaptor for Sennebogen/euro pick-up	<input type="checkbox"/>
<b>Hydraulics</b>	
Auxiliary valve 1 on tool carrier	<input checked="" type="checkbox"/>
3rd hydr. working circuit on tool carrier	<input type="checkbox"/>
Auxiliary valve 2 on rear	<input type="checkbox"/>
Continuous function of auxiliary valve 1	<input type="checkbox"/>
Electric hydraulic tank pre-heating	<input type="checkbox"/>
Bio hydraulic oil	<input type="checkbox"/>
Low-temperature hydraulic fluid	<input type="checkbox"/>

Cargo T955	
<b>Cab</b>	
Comfort lift cab with suspension system	<input checked="" type="checkbox"/>
Full-length panoramic windscreen	<input checked="" type="checkbox"/>
Windscreen made from shatter-proof glass	<input checked="" type="checkbox"/>
Side windows including doors with Hammerglass® safety glass	<input type="checkbox"/>
Roof window made from shatter-proof glass	<input checked="" type="checkbox"/>
Joystick on armrest	<input checked="" type="checkbox"/>
Comfort driver's seat air-sprung, heated	<input checked="" type="checkbox"/>
Height and tilt-adjustable steering column	<input checked="" type="checkbox"/>
Air-conditioning	<input type="checkbox"/>
Sunblind for roof window	<input type="checkbox"/>
Sunblind for windscreen	<input type="checkbox"/>
Wipers and washers for roof window	<input type="checkbox"/>
Wipers and washers for rear window	<input type="checkbox"/>
Protective grille for roof window, FOPS Level 1	<input type="checkbox"/>
Protective grille for roof window, FOPS Level 2	<input type="checkbox"/>
Radio including USB and SD interface, MP3 and Bluetooth	<input type="checkbox"/>
USB port with charging function	<input checked="" type="checkbox"/>
Camera system	<input type="checkbox"/>
Active charcoal filter	<input type="checkbox"/>
<b>Lighting</b>	
Approved lighting set	<input checked="" type="checkbox"/>
2 working lights at front of cab, LED	<input checked="" type="checkbox"/>
Working lights at rear of cab, LED	<input checked="" type="checkbox"/>
2 headlights at ground boom, LED	<input type="checkbox"/>
All-round lighting bundle	<input type="checkbox"/>
1 rotating beacon	<input type="checkbox"/>
Protective grille for headlights at front	<input type="checkbox"/>
<b>Chassis</b>	
Levelling on front axle	<input type="checkbox"/>
Swing axle lock on rear axle	<input type="checkbox"/>
Front axle, all-wheel and crab steering	<input checked="" type="checkbox"/>
<b>Additional equipment</b>	
Trailer hitch with auto coupling, height-adjustable	<input type="checkbox"/>
Ball coupling, height adjustable	<input type="checkbox"/>
Piton-hitch, height adjustable	<input type="checkbox"/>
Pick-up hitch	<input type="checkbox"/>
Air pressure brake for trailer control	<input type="checkbox"/>
7-pin socket for trailer operation 12 V	<input type="checkbox"/>
7-pin socket for trailer operation 24 V	<input type="checkbox"/>
7-pin socket on boom head	<input type="checkbox"/>
Mirrors right and rear	<input checked="" type="checkbox"/>
Automatic central lubrication system	<input type="checkbox"/>
Body paint in choice of RAL colour	<input type="checkbox"/>
Protection for use in aggressive environments	<input type="checkbox"/>

# Technical specifications.

Cargo T955		
<b>Performance characteristics</b>		
Max. lift height	mm	8500
Max. load (LSP 600 mm)	kg	5500
Max. load at max. height	kg	4850
Max. load at max. outreach	kg	2400
Max. extension	mm	4350
Tractive power	kN	90
Breakaway torque on the bucket	kN	85
<b>Engine</b>		
Rated power ECE R 120	kW/hp	123/167
Maximum power ECE R 120	kW/hp	126/171
No. of cylinders	Number	4
Cubic capacity	cm³	4500
Rated speed	rpm	2200
Max. torque	Nm	763
Fuel level	litres	160.0
AdBlue level	litres	16.0
<b>Transmission</b>		
Transmission type		CompactDrive
Max. road speed, standard	km/h	20
Max. road speed, Option 1	km/h	30
Max. road speed, Option 2	km/h	40
Max. road speed, reverse	km/h	20 (30/40)
<b>Hydraulics</b>		
Powershift variable flow pump	l/min	200
Working pressure	bar	310
<b>Electrical features</b>		
Batteries	Number	2
Battery power	Ah/V	105 / 24
<b>Tyres</b>		
Standard tyres		460/70 -24
1. Optional tyres		500/70 R24
2. Optional tyres		600/55 -26.5
<b>Dimensions</b>		
Overall length including tool carrier	mm	5635
Overall height, cab down	mm	2670
Overall height, cab up	mm	4550
Overall width with standard tyres	mm	2475
Overall width with max. tyres	mm	2750
Cab width	mm	950
Distance from middle of front axle to front of tool carrier	mm	1335
Distance from middle of rear axle to rear of machine	mm	1045
Max. ground clearance	mm	425
Wheelbase	mm	3250
Track width	mm	2050
Rear startup angle	°	33
Min. turning radius with standard tyres	m	4.4
<b>Weights</b>		
Unladen weight (standard equipment, full tanks, with driver)	kg	11800
Max. trailer load of towing hitch	kg	3000
Max. trailer load of towing hitch, height-adjustable (optional)	kg	15000

\* Please refer to the Settings for equipment variants