

# Uitvoeringen en technische gegevens.

		Tigo 45 PR	Tigo 50 PR	Tigo 60 PR	Tigo 65 VR	Tigo 75 VR	Tigo 65 XR	Tigo 75 XR	Tigo 90 XR	Tigo 100 XR
<b>Technische gegevens</b>										
Volume vlg. DIN 11741	m³	31	31	36	37	42,5	38	44	50	54
Volume vlg. DIN 11741 incl. doseerwalsen	m³	29	29	34	35	40,5	36	42	48	52
Volume vlg. DIN 11741 bij gedemonteerde doseerwalsen	m³	32	32	37	37	42,5	38	44	50	54
Volume bij gemiddelde verdichting	m³	45	50	60	65	75	65	75	90	100
Vereist vermogen	kW/pk	96/130	96/130	110/150	110/150	110/150	132/180	147/200	169/230	184/250
Leeggewicht in basisuitvoering	kg	6.650	7.550	7.950	8.950	9.950	9.200	10.200	11.900	12.300
Leeggewicht incl. doseerwalsen in basisuitvoering	kg	7.050	8.050	8.450	9.450	10.450	9.700	10.700	12.400	12.800
Max. toegelaten totaalgewicht*	kg	17.000/18.000	20.000/22.000	20.000/24.000	24.000	24.000	24.000	24.000	31.000	31.000
Totale breedte	m	2,52	2,52	2,52	2,75	2,75	2,75	2,75	2,95	2,95
Totale lengte	m	7,75	7,75	8,75	8,77	9,77	8,75	9,75	10,75	11,75
Totale lengte incl. doseerwalsen	m	8,38	8,38	9,38	8,77	9,77	8,75	9,75	10,75	11,78
Totale hoogte	m	3,85	3,92	3,92	3,92	4,00	4,00	4,00	4,00	4,00
Breedte laadvloer	m	2,16	2,16	2,16	2,36	2,36	2,36	2,36	2,36	2,36
Lengte laadvloer	m	5,00	5,00	6,00	6,10	7,10	6,10	7,10	8,10	9,10
Spoorbreedte	m	1,95	2,00	2,00	2,05	2,05	2,05	2,05	2,05	2,05
Toegestane oplegdruk	kg	2.000/3.000	2.000/4.000	2.000/4.000	4.000	4.000	4.000	4.000	4.000	4.000
Tandbalken pick-up	Aantal	7	7	7	7	7	7	7	7	7
Werkbreedte pick-up vlg. DIN	cm	190/200	190/200	190/200	200	200	220	220	220	220
Tandafstand	mm	54	54	54	54	54	54	54	54	54
Bodemvrijheid pick-up	cm	40-70	40-70	40-70	40-80	40-80	40-80	40-80	40-80	40-80
De rotor		■	■	■	■	■	■	■	■	■
Diameter rotor	mm	800	800	800	800	800	800	800	800	800
Tandenrijen rotor	Aantal	7	7	7	7	7	7	7	7	7
Maximaal aantal messen	Aantal	40	40	40	40	40	45	45	45	45
Theoretische snijlengte	mm	37	37	37	37	37	37	37	37	37
Goedkeuring 40 km/h		□	□	□	□	□	□	□	□	□
Goedkeuring 60 km/h*		□	□	□	□	□	□	□	□	□
18,5 t bogie-tandemonderstel 22,5"		■								
22 t bogie-tandemonderstel 22,5"			■	■						
24 t bogie-tandemonderstel 26,5"				□	■					
24 t hydropneumatisch geveerd tandemonderstel, banden R26,5				□	□	■	■	■		
24 t hydropneumatisch geveerd tandemonderstel, banden R30,5					□	□	□	□		
31 t hydropneumatisch geveerd tridemonderstel, banden R26,5									■	■
Fendt Stability Cornrol (FSC)				□	□	□	■	■	■	■
Hydraulisch remsysteem		□	□	□	□	□	□	□	□	□
Luchtdrukremsysteem		□	□	□	□	□	□	□	□	□
Lastafhankelijk remsysteem		■	■	■	■	■	■	■	■	■
Naloopbesturing		□	■	■	■	■	■	■	■	■
<b>Dissel</b>										
Hydropneumatische disselvering		□	□	□	□	□	■	■	■	■
Knikdissel-positieregeling		□	□	□	□	□	□	□	□	□
<b>Pick-up</b>										
XL-pick-up hydraulisch aangedreven		□	□	□	■	■	■	■	■	■
Werkbreedte XL-pick-up vlg. DIN	mm	2000	2000	2000	2000	2000	2200	2200	2200	2200
Heavy-duty-aandrijflijn							■	■	■	■
Tastrol achter pick-up, in midden wagen		□	□	□	□	□	□	□	□	□
Hydraulische pick-up-ontlasting		□	□	□	□	□	□	□	□	□

## Snij-inrichting en rotor

	Tigo 45 PR	Tigo 50 PR	Tigo 60 PR	Tigo 65 VR	Tigo 75 VR	Tigo 65 XR	Tigo 75 XR	Tigo 90 XR	Tigo 100 XR
Afdekplaat invoerkanaal	□	□	□	□	□	□	□	□	□
Zijdelings uitzwenkende messenbalk	□	■	■	■	■	■	■	■	■
Individuele mesbeveiliging	■	■	■	■	■	■	■	■	■
Centrale mesvergrendeling	■	■	■	■	■	■	■	■	■
Messenslijpinrichting	□	□	□	□	□	□	□	□	□

## Opbouw laadbak

	Tigo 45 PR	Tigo 50 PR	Tigo 60 PR	Tigo 65 VR	Tigo 75 VR	Tigo 65 XR	Tigo 75 XR	Tigo 90 XR	Tigo 100 XR
Multifunctionele voorwand	■	■	■	■	■	■	■	■	■
Zonder doseerwalsen	■	■	■	■	■	■	■	■	■
2 Doseerwalsen	□	□	□	□	□	□	□	□	□
3 Doseerwalsen	□	□	□	□	□	□	□	□	□
Voorraan 250 mm verlaagde vloer	■	■	■	■	■	■	■	■	■
Tweetrapsmotor bodemketting	□	□	□	□	□	■	■	■	■
Terutdraaifunctie van de bodemketting	□	□	□	□	□	□	□	□	□
Afscherming bodemkettingaandrijving	□	□	□	■	■	■	■	■	■
Camera in laadbak	□	□	□	□	□	□	□	□	□
Weegstelsysteem		□	□	□	□	□	□	□	□
Afdeksysteem**	□	□	□	□	□	□	□	□	□
3 led-werklampen	□	□	□	□	□	■	■	■	■
2 extra achteruitrijlichten (led)	□	□	□	□	□	□	□	□	□
Toegangsdeur laadbak	■	■	■	■	■	■	■	■	■

## Onderstel

	Tigo 45 PR	Tigo 50 PR	Tigo 60 PR	Tigo 65 VR	Tigo 75 VR	Tigo 65 XR	Tigo 75 XR	Tigo 90 XR	Tigo 100 XR
Gedwongen besturing, hydraulisch	□	□	□	□	□	□	□	□	□
Gedwongen besturing, elektrisch	□	□	□	□	□	□	□	□	□
Liftas							□	□	□

## Bediening

	Tigo 45 PR	Tigo 50 PR	Tigo 60 PR	Tigo 65 VR	Tigo 75 VR	Tigo 65 XR	Tigo 75 XR	Tigo 90 XR	Tigo 100 XR
ISOBUS Fendt-Varioterminal (12")	■	■	■	■	■	■	■	■	■
Tigo-bedieningskast (folietoetsen)	□	□	□	□	□	□	□	□	□
VarioFill laad-en-los-automaat	■	■	■	■	■	■	■	■	■
TIM-doorvoerregeling				□	□	□	□	□	□

## Bandenmaten

	Tigo 45 PR	Tigo 50 PR	Tigo 60 PR	Tigo 65 VR	Tigo 75 VR	Tigo 65 XR	Tigo 75 XR	Tigo 90 XR	Tigo 100 XR
620/40 R22,5 Flotation Pro	□								
710/35 R22,5 Country King	□								
710/40 R22,5 Flotation Pro		□	□						
710/45 R22,5 Flotation Trac		□	□						
710/50 R26,5 Flotation Pro			□	□	□	□	□	□	□
750/45 R26,5 Flotation Trac				□	□	□	□	□	□
750/45 R26,5 Alliance 380				□	□	□	□	□	
750/45 R26,5 Alliance 380 - Tridem							□	□	□
800/45 R30,5 Alliance 885				□	□	□	□	□	□
800/45 R26,5 Flotation Pro				□	□	□	□	□	□
800/45 R30,5 Flotation Trac				□	□	□	□	□	□