



# Equipment variants and technical details.

		5275 C S5	5275 C PL	5275 C PLI S5	5275 C SL
<b>Engine</b>					
AGCO Power Engine		■	■	■	■
emission stage V / Stage 5		■	■	■	■
Emission stage	Stage	5 / V	5 / V	5 / V	5
Cylinders	number	6	6	6	6
Displacement	litres	7.4	7.4	7.4	7.4
Max. performance with PowerBoost (ECE R 120)	kW/hp	225/306	225/306	225/306	225/306
Fuel tank capacity	litres	620	620	620	620
AdBlue tank capacity	litres	80	80	80	80

		5275 C S5	5275 C PL	5275 C PLI S5	5275 C SL
<b>Chassis</b>					
Hydrostatic drive		■	■	■	■
Gear steps	number	4	4	4	4
Mechanical gear shift		■	■	■	■
Max. driving speed*	km/h	25	25	25	30
Four-wheel drive		□	□	■	■
Atrak crawler track					
ParaLevel slope compensation			■	■	
ParaLevel Integrale slope compensation				■	
Superlevel slope compensation****					38.0

		5275 C S5	5275 C PL	5275 C PLI S5	5275 C SL
<b>Cab</b>					
Skyline cab		■	■	■	■
Air-suspended driver seat		■	■	■	■
Automatic climate control		■	■	■	■
Heating		■	■	■	■
Electrically adjustable heated exterior mirrors		■	■	■	■
Additional wide-angle mirror		■	■	■	■
Radio		□	□	□	□
Multimedia navigation		□	□	□	□
Rear-view camera		■	■	■	■
Cooler compartment integrated into the passenger seat		■	■	■	■
Loss indicator		■	■	■	■

		5275 C S5	5275 C PL	5275 C PLI S5	5275 C SL
<b>Fendt Variotronic</b>					
Fendt Variotronic		■	■	■	■
Fendt Varioterminal 10.4*		■	■	■	■
Fendt VarioGuide		□	□	□	□
Fendt Connect		□	□	□	□
Yield and moisture measurement		□	□	□	□
Yield mapping		□	□	□	□

<b>Weights and dimensions</b>		5275 C S5	5275 C PL	5275 C PLI S5	5275 C SL
Length without table	m	9.04	9.0	9.0	9.13
Width without table, standard tyres	m	3.65	3.55	3.55	3.95
Weight base machine, without table, without optional equipment	kg	13500	14800	15200	15200
Height	m	4.0	4.0	4.0	4.3

<b>Tyres</b>		5275 C S5	5275 C PL	5275 C PLI S5	5275 C SL
Drive axle tyres (standard)		800/65R32	800/65R32	800/65R32	650/75R32
Steering axle tyres (standard)		460/70R24	540/65R24	540/65R24	460/70R24

<b>Transport widths</b>		5275 C S5	5275 C PL	5275 C PLI S5	5275 C SL
Atrak crawler track (24" - 610 mm)	mm				
800/65R32 (< 3.5m)	mm	3490	3490	3490	
800/65R32	mm	3645	3550	3550	
710/75R32	mm	3400	3400	3400	
650/75R32	mm	3280	3290	3315	

	5275 C Rice S5	6335 C	6335 C S5	6335 C PL	6335 C PL S5	6335 C PLI	6335 C PLI S5	6335 C Rice	6335 C Rice S5
<b>Engine</b>									
AGCO Power Engine	■	■	■	■	■	■	■	■	■
emission stage V / Stage 5	■	■	■	■	■	■	■	■	■
Emission stage	5 / V	4f	5 / V	4f	5 / V	4f	5 / V	4f	5 / V
Cylinders	6	6	6	6	6	6	6	6	6
Displacement	7.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
Max. performance with PowerBoost (ECE R 120)	225/306	265/360	265/360	265/360	265/360	265/360	265/360	265/360	265/360
Fuel tank capacity	620	620	620	620	620	620	620	620	620
AdBlue tank capacity	80	80	80	80	80	80	80	80	80

	5275 C Rice S5	6335 C	6335 C S5	6335 C PL	6335 C PL S5	6335 C PLI	6335 C PLI S5	6335 C Rice	6335 C Rice S5
<b>Chassis</b>									
Hydrostatic drive	■	■	■	■	■	■	■	■	■
Gear steps	4	4	4	4	4	4	4	4	4
Mechanical gear shift	■	■	■	■	■	■	■	■	■
Max. driving speed*		25	25	25	25	25	25		
Four-wheel drive		□	■	□	□	■	■		
Atrak crawler track		□	□						
ParaLevel slope compensation				■	■	■	■		
ParaLevel Integrale slope compensation						■	■		
Superlevel slope compensation****									

	5275 C Rice S5	6335 C	6335 C S5	6335 C PL	6335 C PL S5	6335 C PLI	6335 C PLI S5	6335 C Rice	6335 C Rice S5
<b>Cab</b>									
Skyline cab	■	■	■	■	■	■	■	■	■
Air-suspended driver seat	■	■	■	■	■	■	■	■	■
Automatic climate control	■	■	■	■	■	■	■	■	■
Heating	■	■	■	■	■	■	■	■	■
Electrically adjustable heated exterior mirrors	■	■	■	■	■	■	■	■	■
Additional wide-angle mirror	■	■	■	■	■	■	■	■	■
Radio	□	□	□	□	□	□	□	□	□
Multimedia navigation	□	□	□	□	□	□	□	□	□
Rear-view camera	■	■	■	■	■	■	■	■	■
Cooler compartment integrated into the passenger seat	■	■	■	■	■	■	■	■	■
Loss indicator	■	■	■	■	■	■	■	■	■

	5275 C Rice S5	6335 C	6335 C S5	6335 C PL	6335 C PL S5	6335 C PLI	6335 C PLI S5	6335 C Rice	6335 C Rice S5
<b>Fendt Variotronic</b>									
Fendt Variotronic	■	■	■	■	■	■	■	■	■
Fendt Varioterminal 10.4*	■	■	■	■	■	■	■	■	■
Fendt VarioGuide	□	□	□	□	□	□	□	□	□
Fendt Connect	□	□	□	□	□	□	□	□	□
Yield and moisture measurement	□	□	□	□	□	□	□	□	□
Yield mapping	□	□	□	□	□	□	□	□	□

<b>Weights and dimensions</b>		5275 C Rice S5	6335 C	6335 C S5	6335 C PL	6335 C PL S5	6335 C PLI	6335 C PLI S5	6335 C Rice	6335 C Rice S5
Length without table	m	9.04	9.04	9.04	9.0	9.0	9.0	9.0	9.04	9.04
Width without table, standard tyres	m		3.9	3.9	3.82	3.82	3.87	3.87		
Weight base machine, without table, without optional equipment	kg	13500	14000	14000	15300	15300	15700	15700	14000	14000
Height	m	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0

<b>Tyres</b>		5275 C Rice S5	6335 C	6335 C S5	6335 C PL	6335 C PL S5	6335 C PLI	6335 C PLI S5	6335 C Rice	6335 C Rice S5
Drive axle tyres (standard)		800/65R32	800/65R32	800/65R32	800/65R32	800/65R32	800/65R32	800/65R32		
Steering axle tyres (standard)		540/65R24	460/70R24	460/70R24	540/65R24	540/65R24	540/65R24	540/65R24		

<b>Transport widths</b>		5275 C Rice S5	6335 C	6335 C S5	6335 C PL	6335 C PL S5	6335 C PLI	6335 C PLI S5	6335 C Rice	6335 C Rice S5
Atrak crawler track (24" - 610 mm)	mm		3490	3490						
800/65R32 (< 3.5m)	mm	3490			3770	3770				
800/65R32	mm	3645	3900	3900	3823	3823	3870	3870	3900	3900
710/75R32	mm	3400	3700	3700	3683	3683			3700	3700
650/75R32	mm	3280	3485	3485	3498	3498			3485	3485