

Equipment variants.*

	Power	Profi	Profit+
Engine			
Reversible fan	□	□	□
Preheater unit (engine, transmission oil)	□	□	□
Transmission			
Vario TMS - Tractor Management System	■	■	■
Shuttle function, stop-and-go function	■	■	■
Cruise control	■	■	■
Guidance system			
Guidance system basic package			■
Standard Trimble / NovAtel			□
RTK Trimble / NovAtel			□
TI Headland (TI Auto & TI Turn Assistant)			□
Contour Assistant			□
Implement Slope Compensation			□
Agronomy			
Agronomy basic package			□
Telemetry			
Telemetry basic package	□	□	□
Smart Connect			□
Machine control			
Machine control basic package		□	□
Section Control			□
Variable Rate Control			□
Fendt Implement Management (TIM)			□
Fendt Implement Management (TIM-Steering)			□
Vario operation			
Multi-function joystick with cruise control, engine speed memory, automatic modes, controls for hydraulics	■	■	■
3L joystick		□	□
Individual Operation Manager – flexible key assignment	■	■	■
Digital Dashboard	■	■	■
12" terminal with touchscreen and key control		□	■
Fendt Active steering		□	■
Cab			
Comfort cab	■	■	■
Mechanical cab suspension	□	■	■
Comfort seat, air sprung	■	■	■
Instructor seat	■	■	■
Height and tilt-adjustable steering column	■	■	■
Air-conditioning	□	■	■
Integrated automatic climate control	□	□	□
Climate-controlled storage compartment	■	■	■
Hinged front/rear windows	■	■	■
Rear window wash/wipe	□	□	□
Ext. rearview mirror, mechanically adjustable	■	■	■
Auxiliary device holder	□	□	□
Fendt Reaction steering system	■	■	■
Self-cancelling indicators	■	■	■
Brake level device	□	□	□
Electric battery disconnect switch	□	□	□
Roof window with roller shade	■	■	■

	Power	Profi	Profit+
Lighting			
Bi-halogen headlights	■	■	■
Auxiliary lights front	□	□	□
Work lights A-pillar	□	□	□
A-pillar LED work lights	□	□	□
Rear roof work lights	■	■	■
Roof rear LED work lights	□	□	□
Front roof work lights	□	□	□
Roof front LED work lights	□	□	□
LED rear lights	□	□	□
Daylight running light	□	■	■
LED rotating beacons	□	□	□
Chassis			
Front axle suspension self-levelling, anti-roll control, lockable	□	□	□
Compressed air system 2-circuit system	□	□	□
4WD / differential locks			
Automatic all-wheel drive and differential locking with steering angle sensors	■	■	■
Automatic front differential lock	■	■	■
Power lift			
Sa front power lift, with external control (separate valve)	□	□	□
Comfort front power lift da, with position control, external controls	□	□	□
Comfort front power lift da, with position control and relief control, external controls	□	□	□
Electrohydraulic power lift sa (EHR), with external controls	■	■	■
Shock load stabilising, electro-hydraulic power lift control	■	■	■
PTO			
Front: 540E rpm	□	□	□
Front: 1000 rpm	□	□	□
Rear PTO 540/WZW/1000 rpm	□	□	□
Rear PTO 540/540E/1000 rpm	■	■	■
External controls for rear PTO	■	■	■
Hydraulics			
EHS valve actuation crossgate lever, multi-function joystick	□	■	■
EHS valve actuation linear module	□	■	■
External control for hydraulic control unit at rear	□	□	□
Hydraulic tandem pump, hydraulic oil cooler (42+ 33 l/min)	■		
Load sensing system with axial piston pump (33+71 l/min)	□	■	■
1st and 2nd EHS valve at rear	■	■	■
3rd EHS valve at rear	□	□	□
4th EHS valve at rear or 3rd EHS valve at rear and 1st EHS valve in front	□	□	□
Hydraulic power beyond connection	□	□	□
Return rear	■	■	■
Unpressurised rear return flow	□	□	□
CUP coupling rear	□	□	□
Additional equipment			
Manual hitch	■	■	■
Automatic trailer hitch with remote control, rear	□	□	□
Ball coupling, height adjustable	□	□	□
Hitch	□	□	□
Drawbar	□	□	□
Piton-fix	□	□	□
Front weights, various sizes	□	□	□
Wheel weights, rear wheels	□	□	□
Pivoting front wheel mudguard	□	□	□
Front loader			
Front loader attachment parts	□	□	□
Front loader Cargo 3X/65	□	□	□

Technical specifications.

		207 Vario	208 Vario	209 Vario	210 Vario	211 Vario
Engine						
Rated power ECE R 120	kW/hp	53/72	60/82	67/91	73/99	77/105
Rated power with DP ECE R 120 (approval rating)	kW/hp					84/114
Maximum power ECE R 120	kW/hp	58/79	62/84	69/94	77/104	84/114
Maximum power with DP ECE R 120	kW/hp					91/124
Cubic capacity	cm³	3300	3300	3300	3300	3300
Rated speed	rpm	2100	2100	2100	2100	2100
Max. torque at 1600 rpm	Nm	328	348	389	428	
Max. torque with DP at 1600 rpm	Nm					508
Fuel level	litres	125.0	125.0	125.0	125.0	125.0
AdBlue tank	litres	16.0	16.0	16.0	16.0	16.0
Transmission and PTO						
Transmission type		ML75	ML75	ML75	ML75	ML75
Speed range forward	km/h	0.02-40	0.02-40	0.02-40	0.02-40	0.02-40
Speed range reverse	km/h	0.02-25	0.02-25	0.02-25	0.02-25	0.02-25
Rear PTO		540/540E/1000	540/540E/1000	540/540E/1000	540/540E/1000	540/540E/1000
Rear PTO option (including ground speed PTO)		540/1000/4,0	540/1000/4,0	540/1000/3,8	540/1000/3,8	540/1000/3,8
Front PTO option		1000	1000	1000	1000	1000
Power lift and hydraulics						
Dual hydraulic pump	l/min	33+42	33+42	33+42	33+42	33+42
Variable flow pump	l/min	33+71	33+71	33+71	33+71	33+71
Max. valves (front/centre/rear)	number	0/0/4	0/0/4	0/0/4	0/0/4	0/0/4
Max. valves available as an option (front/centre/rear)	number	1/0/3	1/0/3	1/0/3	1/0/3	1/0/3
Max. available hydraulic oil volume	litres	34	34	34	34	34
Max. lift capacity of rear power lift	daN	4204	4204	4204	4204	4204
Max. lift capacity of front power lift	daN	2540	2540	2540	2540	2540
Tyres						
Front tyres (standard)		320/70R24	320/70R24	380/70R24	380/70R24	440/65R24
Standard tyres rear		420/85R30	480/70R30	480/70R34	480/70R34	540/65R34
1st option for front tyres		320/70R24	320/70R24	320/70R24	320/70R24	320/70R24
1st option for rear tyres		480/70R30	420/85R30	420/85R30	420/85R30	420/85R30
2nd option for front tyres		380/70R24	380/70R24	320/70R24	320/70R24	320/70R24
2nd option for rear tyres		480/70R34	480/70R34	480/70R30	480/70R30	480/70R30
3rd option for front tyres		440/65R24	440/65R24	440/65R24	440/65R24	380/70R24
3rd option for rear tyres		540/65R34	540/65R34	540/65R34	540/65R34	480/70R34
Dimensions						
Front track width (standard tyres)	mm	1500	1500	1690	1690	1690
Rear track width (standard tyres)	mm	1510	1655	1660	1660	1660
Overall width with standard tyres	mm	1970	2170	2170	2170	2186
Overall length	mm	4119	4119	4119	4119	4119
Total height of driver's cab with standard tyres without Fendt Guide	mm	2570	2570	2620	2620	2620
Total height of driver's cab with standard tyres with Fendt Guide	mm	2660	2660	2710	2710	2710
Max. ground clearance	mm	475	475	475	475	475
Wheelbase	mm	2370	2370	2370	2370	2370
Weights						
Unladen weight (base tractor with cab - full tanks, without driver)	kg	4100.0	4140.0	4220.0	4220.0	4280.0
Max. permissible overall weight	kg	7500.0	7500.0	7500.0	7500.0	7500.0

* Please refer to the Settings for equipment variants