

# Equipment variants.\*

	Power	Power+	Profi	Profi+
<b>Engine</b>				
Fuel pre-filter (heated)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Preheater unit (engine, transmission, hydraulic oil)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Transmission</b>				
Shuttle function, stop-and-go function	■	■	■	■
Acoustic signal when reversing	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Guidance system</b>				
Guidance system basic package		■		■
Standard Trimble / NovAtel		<input type="checkbox"/>		<input type="checkbox"/>
RTK Trimble / NovAtel		<input type="checkbox"/>		<input type="checkbox"/>
TI Headland (TI Auto & TI Turn Assistant)				<input type="checkbox"/>
Contour Assistant		<input type="checkbox"/>		<input type="checkbox"/>
Implement Slope Compensation		<input type="checkbox"/>		<input type="checkbox"/>
<b>Agronomy</b>				
Agronomy basic package		<input type="checkbox"/>		■
<b>Telemetry</b>				
Telemetry basic package	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	■
Smart Connect				<input type="checkbox"/>
<b>Machine control</b>				
Machine control basic package		■	■	■
Front implement control			<input type="checkbox"/>	<input type="checkbox"/>
Section Control		<input type="checkbox"/>		<input type="checkbox"/>
Variable Rate Control		<input type="checkbox"/>		<input type="checkbox"/>
Fendt Implement Management (TIM)				<input type="checkbox"/>
Fendt Implement Management (TIM-Steering)		<input type="checkbox"/>		<input type="checkbox"/>
<b>Vario operation</b>				
Multi-function joystick with cruise control, engine speed memory, automatic modes, controls for hydraulics	■	■	■	■
3L joystick		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Individual Operation Manager – flexible key assignment	■	■	■	■
Digital Dashboard	■	■	■	■
12" terminal with touchscreen and key control	<input type="checkbox"/>	■	■	■
Second 12" terminal in roof			<input type="checkbox"/>	<input type="checkbox"/>
Electronic immobiliser	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Cab</b>				
Active charcoal filter	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Mechanical cab suspension	■	■	■	■
Pneumatic cab suspension	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Super comfort seat 3-point belt	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Comfort seat, air sprung	■	■	■	■
Super Comfort Seat, air sprung	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Super comfort seat Evolution dynamic / CA	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Super Comfort Seat Evolution dynamic DuMo/CA	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Super Comfort Seat Evolution dynamic DuMo leather / CA			<input type="checkbox"/>	<input type="checkbox"/>
Instructor seat	■	■		
Comfort instructor seat			■	■
Air-conditioning	■	■	■	■
Integrated automatic climate control	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Split windscreen and door on right	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Continuous windscreen	■	■	■	■
One-piece windscreen and door on right	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Rear window heated	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Segment wipers front	■	■	<input type="checkbox"/>	<input type="checkbox"/>
300°-front windscreen wipers (with continuous windscreen)	<input type="checkbox"/>	<input type="checkbox"/>	■	■
Rear window wash/wipe	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Rear view mirror and wide-angle mirror electrically adjustable, heated			<input type="checkbox"/>	<input type="checkbox"/>
Terminal bracket	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radio mounting kit with two stereo speakers	■	■	■	■
Infotainment bundle + 4.1 sound system			<input type="checkbox"/>	<input type="checkbox"/>
4 USB ports			<input type="checkbox"/>	<input type="checkbox"/>

	Power	Power+	Profi	Profi+
<b>Chassis</b>				
Front axle suspension self-levelling, lockable	■	■	■	■
Steering brake	■	■	■	■
Automatic trailer steering axle lock			<input type="checkbox"/>	<input type="checkbox"/>
Compressed air system 2-circuit system	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Compressed air Duomatic coupling	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Power lift</b>				
Sa front power lift, with external control (separate valve)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Comfort front power lift da, with position control, external controls	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Comfort front power lift da, with position control and relief control, external controls	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Electrohydraulic power lift da (EHR), with external controls			<input type="checkbox"/>	<input type="checkbox"/>
Electrohydraulic power lift sa (EHR), with external controls	■	■	■	■
<b>PTO</b>				
Front: 1000 rpm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Rear PTO 540/540E/1000 rpm	■	■	■	■
Rera PTO 540E/1000/1000E rpm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Rear: Flanged PTO 540/1,000 rpm	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Hydraulics</b>				
EHS valve actuation crossgate lever, multi-function joystick	<input type="checkbox"/>	■	■	■
EHS valve actuation linear module	<input type="checkbox"/>	■	■	■
External control for hydraulic control unit at rear	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Load sensing system with axial piston pump (75 l/min)	■	■		
Load sensing system with axial piston pump (110 l/min)	<input type="checkbox"/>	<input type="checkbox"/>	■	■
Load sensing system with axial piston pump (158 l/min)			<input type="checkbox"/>	<input type="checkbox"/>
1st and 2nd EHS valve at rear	■	■	■	■
3rd EHS valve at rear	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4th EHS valve at rear	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5th EHS valve at rear			<input type="checkbox"/>	<input type="checkbox"/>
1st front EHS valve	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2nd front EHS valve			<input type="checkbox"/>	<input type="checkbox"/>
Hydraulic power beyond connection	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Unpressurised rear return flow	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Double connect-under-pressure lever couplings rear	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
CUP coupling rear	■	■	■	■
Bio hydraulic oil	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<b>Additional equipment</b>				
Manual hitch	■	■	■	■
Automatic trailer hitch with remote control, rear	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Ball coupling, height adjustable	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Ball coupling in the bottom hitch	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Hitch	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Drawbar	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Piton-fix	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Comfort ballast for front-end weight (not available with front power lift)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wheel weights, rear wheels	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Forced steering (one or two-sided)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Pivoting front wheel mudguard	<input type="checkbox"/>	<input type="checkbox"/>	■	■
<b>Front loader</b>				
Front loader attachment parts	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Front loader Cargo 4X/75	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Front loader Cargo 4X/75 - third valve		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Front loader Cargo 4X/80	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Front loader Cargo 4X/80 - third valve		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Front loader Cargo Profi 4X/80			<input type="checkbox"/>	<input type="checkbox"/>
Front loader Cargo Profi 4X/80 - third valve			<input type="checkbox"/>	<input type="checkbox"/>

# Technical specifications.

		512 Vario	513 Vario	514 Vario	516 Vario
<b>Engine</b>					
Rated power ECE R 120	kW/hp	91/124	98/133	110/150	120/163
Maximum power ECE R 120	kW/hp	96/131	104/141	115/156	126/171
Cubic capacity	cm³	4038	4038	4038	4038
Rated speed	rpm	2100	2100	2100	2100
Max. torque at 1500 rpm	Nm	564	604	663	699
Torque rise	%	36.0	35.0	33.0	28.0
Fuel level	litres	298.0	298.0	298.0	298.0
AdBlue tank	litres	31.0	31.0	31.0	31.0
<b>Transmission and PTO</b>					
Transmission type		ML 90	ML 90	ML 90	ML 90
Speed range 1	km/h	0,02-28	0,02-28	0,02-28	0,02-28
Speed range 1 - reverse	km/h	0,02-17	0,02-17	0,02-17	0,02-17
Speed range 2	km/h	0,02-50	0,02-50	0,02-50	0,02-50
Speed range 2 - reverse	km/h	0,02-33	0,02-33	0,02-33	0,02-33
Top speed	km/h	50	50	50	50
Rear PTO		540/ 540E/ 1000	540/ 540E/ 1000	540/ 540E/ 1000	540/ 540E/ 1000
Rear PTO option		540E/ 1000 /1000E	540E/ 1000 /1000E	540E/ 1000 /1000E	540E/ 1000 /1000E
Front PTO option		1000	1000	1000	1000
<b>Power lift and hydraulics</b>					
Variable flow pump	l/min	75	75	75	75
Variable flow pump option 1	l/min	110	110	110	110
Variable flow pump option 2	l/min	158	158	158	158
Max. valves (front/centre/rear) Power / Power+	number	0/0/4 od. 1/0/3	0/0/4 od. 1/0/3	0/0/4 od. 1/0/3	0/0/4 od. 1/0/3
Max. valves (front/centre/rear) Profi / Profi+	Number	2/0/5	2/0/5	2/0/5	2/0/5
Max. available hydraulic oil volume	litres	55	55	55	55
Max. lift capacity of rear power lift	daN	7890	7890	7890	7890
Max. lift capacity of front power lift	daN	3420	3420	3420	3420
<b>Tyres</b>					
Front tyres (standard)		480/65R28	480/65R28	480/70R28	540/65R28
Standard tyres rear		600/65R38	600/65R38	580/70R38	650/65R38
1st option for front tyres		16.9R28	16.9R28	480/65R28	480/65R28
1st option for rear tyres		20.8R38	20.8R38	600/65R38	600/65R38
<b>Dimensions</b>					
Front track width (standard tyres)	mm	1880	1880	1880	1880
Rear track width (standard tyres)	mm	1860	1860	1860	1860
Overall width with standard tyres	mm	2450	2450	2450	2505
Overall length	mm	4453	4453	4453	4453
Max. ground clearance	mm	530	530	530	530
Wheelbase	mm	2560	2560	2560	2560
<b>Weights</b>					
Unladen weight (base tractor with cab - full tanks, without driver)	kg	6050.0	6050.0	6400.0	6400.0
Max. permissible overall weight up to 40 km/h country-specific exception approval required	kg	10500.0	10500.0	10500.0	10500.0
Max. permissible overall weight up to 50 km/h country-specific exception approval required	kg	10500.0	10500.0	10500.0	10500.0

\* Please refer to the Settings for equipment variants