

FENDT CUTTER

Technical Specifications.



Fendt Cutter		2940 FPV	3140 FPV	3340 FPV	310 FZ	262	292	310 TL	
Weights and dimensions	Working width	m	2.86	3.06	3.26	3.06	2.55	2.85	3.06
	Transport width	m	2.78	3.00	3.20	3.00	1.60	1.60	1.64
	Swath width	m	1.20 – 1.40	1.20 – 1.60	1.40 – 1.75	1.10 – 1.35	1.65	1.85	1.95
	Transport length	m	1.65	1.65	1.65	1.40	4.70	4.90	1.90
	Weight	kg	846	874	907	910	763	775	1,105
Power requirement	Power requirement	kW / hp	55 / 75	55 / 75	55 / 75	55 / 75	53 / 72	60 / 82	60 / 82
Attachment	Attachment		CAT II	CAT II	CAT II	CAT II	CAT II + III	CAT II + III	CAT II + III
Cutting unit	Cutting drums		4	4	4	4	4	4	4
	Blades per drum		3	3	3	3	3	3	3
	Inf. adjustable cutting height		■	■	■	■	–	–	–
	Quick-release blade system		■	■	■	■	■	■	■
	Swath disc		■	■	■	■	□	□	□
Hydraulics and PTO	Required hydraulic connections		–	–	–	1 sa	–	–	1 sa, 1 da
	PTO speed	rpm	1,000	1,000	1,000	1,000	1,000	1,000	1,000
	Drive shaft with freewheel		■	■	■	■	■	■	■

FP Front attachment, oscillating linkage
 V Variable cutting height adjustment
 FZ Front attachment, headstock with trailing linkage
 TL TurboLift system

