

Standard and optional equipment  
 Standard: ■  
 Optional: □

FENDT SLICER DISC MOWER

# Equipment variants and technical details.



		Front mowing units					
		Slicer 260 FP	Slicer 260 FPS	Slicer 310 FPK	Slicer 3060 FP	Slicer 3060 FPSL	Slicer 3060 FPKC
<b>Weights and dimensions</b>							
Working width	m	2,50	2,50	3,00	3,00	3,00	3,00
Transport width	m	2,50	2,50	3,00	3,00	3,00	3,00
Swath width	m	1,35	1,35	2,00	2,00	< 1,10	1,45 - 2,20
Transport height	m						
Transport length	m	1,21	1,21	1,20	1,49	1,49	1,58
Weight	kg	474	504	694	770	890	990
<b>Power requirement</b>							
Power requirement	kW/HP	28 / 38	28 / 38	55 / 75	55 / 75	55 / 75	66 / 90
<b>Hitching</b>							
Three-point	Category	II	II	II	II	II	II
Two-point lower links	Category						
<b>Cutting unit</b>							
Cutting discs	Number	4	4	6	6	6	6
Blades per mower disc	Number	2	2	2	2	2	2
Quick-release blade system				■	■	■	■
DriveGuard				■	■	■	■
Mechanical lateral displacement							
Hydraulic lateral displacement			■				
Hydraulic opening/closing of side guard					□	□	□
TurboLift mowing attachment relief							
ISOBUS control							
SafetySwing							
BeMove							
SectionControl							
<b>Hydraulics</b>							
Required sa hydraulic connections	Number						
Required da hydraulic connections	Number		1				
Required hydraulic connections LS	Number						
<b>PTO</b>							
PTO speed	rpm	540 / 1000	540 / 1000	1000	1000	1000	1000
Drive shaft with freewheel		■	■	■	■	■	■
<b>Tyres</b>							
Transport chassis tyres							
<b>Lighting</b>							
Electrical lighting / warning signs				□	□	□	□

Front mowing units							Rear/side mowing units				
Slicer 3060 FPRC	Slicer 310 FQ	Slicer 310 FQ KC	Slicer 310 FQ RC	Slicer 360 FQ***	Slicer 360 FQ KC***	Slicer 360 FQ RC***	Slicer 2460 ISL	Slicer 2870 ISL	Slicer 270 P	Slicer 320 P	Slicer 350 P
3,00	3,12	3,12	3,12	3,62	3,62	3,62	2,42	2,82	2,55	3,00	3,50
3,00	2,99	2,99	2,99	3,49	3,49	3,49	1,80	1,80	2,13	2,13	2,13
1,55 - 1,90							1,65	2,00	1,60	1,80	2,30
	1,88	1,88	1,88	1,88	1,88	1,88	3,30	3,70	2,95	3,43	3,91
1,52							1,35	1,35	1,30	1,30	1,30
1040	950	1238	1238	1020	1374	1374	510	550	630	724	798
64 / 87	63 / 85	85 / 115	85 / 115	70 / 95	96 / 130	96 / 130	37 / 50	44 / 60	40 / 54	45 / 61	50 / 68
II	II	II	II	II	II	II	I + II	I + II	II	II	II
6	6	6	6	7	7	7	6	7	5	6	7
2	2	2	2	2	2	2	2	2	2	2	2
■	■	■	■	■	■	■	■	■	■	■	■
■									■	■	■
	■	■	■	■	■	■					
□	□	□	□	□	□	□					
	■	■	■	■	■	■					
	1	1	1	1	1	1	1	1	1	1	1
1000	1000	1000	1000	1000	1000	1000	540	540	540	540	540
■							■	■	■	■	■
□	□	□	□	□	□	□	□	□	□	□	□

B = Transverse conveyor belt / FP = Front-mounted oscillating linkage / FZ = Front-mounted headstock / ISL = Spur gear drive without inner shoe / KC = Tine conditioner / RC = Roller conditioner / S = Lateral adjustment / SL = Rake / TL = TurboLift system / Number of required hydraulic connections may vary depending on the additional equipment / \*\*\* = Observe country-specific regulations

