

Equipment variants
and technical details.



Front mowers with pendulum support F-series			Front mower with alpine pendulum frame			Front mowers with 3D drawbar						Rear mower with side suspension (ISL)		Rear mower with side suspension		

		Slicer 310 F	Slicer 310 F KC	Slicer 310 F RC	Slicer 260 FP	Slicer 260 FPS	Slicer 310 FPK		Slicer 310 FQ	Slicer 310 FQ KC	Slicer 310 FQ RC	Slicer 360 FQ	Slicer 360 FQ KC	Slicer 360 FQ RC	Slicer 2460 ISL	Slicer 2870 ISL	Slicer 270 P	Slicer 320 P	Slicer 350 P
--	--	--------------	-----------------	-----------------	---------------	----------------	----------------	--	---------------	------------------	------------------	---------------	------------------	------------------	-----------------	-----------------	--------------	--------------	--------------

Weights and dimensions

Working width	m	3,10	3,10	3,10	2,50	2,50	3,00		3,10	3,10	3,10	3,60	3,60	3,60	2,42	2,82	2,55	3,00	3,50
Transport width	m	3,00	3,00	3,00	2,50	2,50	3,00		2,99	2,99	2,99	3,49	3,49	3,49	1,80	1,80	2,13	2,13	2,13
Swath width	m	1,80	1,20 - 2,00	1,20 - 2,00	1,35	1,35	2,00		1,80	1,20-2,00	1,20-2,00	2,30	1,70-2,50	1,70-2,50	1,65	2,00	2,00	2,20	2,60
Transport height	m								1,88	1,88	1,88	1,88	1,88	1,88	3,30	3,70	2,95	3,43	3,91
Transport length	m	1,65	1,74	1,74	1,21	1,21	1,20		2,05	2,05	2,05	2,05	2,05	2,05	1,35	1,35	1,30	1,30	1,30
Weight	kg	710	1015	1045	474	504	694		950	1238	1238	1020	1343	1374	510	550	690	753	833

Power requirement

Power requirement	kW/HP	44/60	55/75	52/70	28/38	28/38	55/75		44/60	56/75	52/70	52/70	67/90	63/85	37/50	44/60	40/54	45/61	50/68
-------------------	-------	-------	-------	-------	-------	-------	-------	--	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

Hitching

Three-point	category	II	II	II	II	II	II		II	II	II	II	II	II	I + II	I + II	II	II	II
-------------	----------	----	----	----	----	----	----	--	----	----	----	----	----	----	--------	--------	----	----	----

Cutting unit

Cutting discs	number	6	6	6	4	4	6		6	6	6	7	7	7	6	7	5	6	7
Blades per mower disc	number	2	2	2	2	2	2		2	2	2	2	2	2	2	2	2	2	2
Quick-release blade system		■	■	■			■		■	■	■	■	■	■	■	■	■	■	■
Compact angle drive					■	■	■										■	■	■
Front wheel drive		■	■	■					■	■	■	■	■	■	■	■			
DriveGuard							■										■	■	■
Mechanical lateral displacement																			
Hydraulic lateral displacement						■			□	□	□	□	□	□					
Hydraulic opening/closing of side guard		□	□	□					□	□	□	□	□	□					
TurboLift mowing attachment relief									■	■	■	■	■	■					
ISOBUS control																			
SafetySwing																			
BeMove																			
RC DUO drive				□							□			□					

Hydraulics

Required sa hydraulic connections	number								1	1	1	1	1	1	1	1	1	1	1
Required da hydraulic connections	number					1													
Flat face coupling									□	□	□	□	□	□					

PTO

PTO speed	rpm	1000 (850)	1000 (850)	1000 (850)	540/1000	540/1000	1000		1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	540	540	540	540	540
Drive shaft with freewheel					■	■	■								■	■	■	■	■
Freilauf im Getriebe		■	■	■					■	■	■	■	■	■					

Lighting

Electrical lighting / warning signs		□	□	□			□		□	□	□	□	□	□			□	□	□
-------------------------------------	--	---	---	---	--	--	---	--	---	---	---	---	---	---	--	--	---	---	---

Assembly

Assembly time approx.	hrs	0,5	0,5	0,5	0,5	0,5	0,5		1,0	1,0	1,0	1,0	1,0	1,0	4,0	4,0	3,0	3,0	3,0
-----------------------	-----	-----	-----	-----	-----	-----	-----	--	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Standard and optional equipment
Standard: ■
Optional: □

Equipment variants
and technical details.



		Slicer 4080 TL	Slicer 4590 TL	Slicer 3160 TLX	Slicer 3160 TLXKC	Slicer 3160 TLXRC	Slicer 3670 TLX		Slicer 3670 TLXKC	Slicer 3670 TLXRC	Slicer 860	Slicer 860 KC	Slicer 860 RC	Slicer 960	Slicer 991 TLKC	Slicer 9314 TLKCB	Slicer 313 TKC	Slicer 313 TRC
Weights and dimensions																		
Working width	m	4,00	4,50	3,10	3,10	3,10	3,60		3,60	3,60	8,30/8,60	8,30/8,60	8,30/8,60	9,30/9,60	9,30	9,30	3,00	3,00
Transport width	m	2,30	2,30	2,50	2,50	2,50	2,80		2,80	2,80	2,99	2,99	2,99	2,99	2,78	2,78	3,00	3,00
Swath width	m	3,30	3,80	1,80	1,20-2,00	1,20-2,00	2,30		1,70-2,50	1,70-2,50	2 x 1,80	2 x 1,20-2,00	2 x 1,20-2,00	2 x 2,30	2 x 1,85-3,25	1,80-3,00	0,90-2,25	1,55-1,90
Transport height	m			3,58	3,58	3,58	3,99		3,99	3,99	3,99	3,99	3,99	3,99	3,99	3,99	7,00	7,00
Transport length	m	5,60	6,10	1,70	2,10	2,10	1,70		2,10	2,10								
Weight	kg	980	1100	1050	1350	1350	1200		1500	1500	1610	2250	2310	1850	2830	3450	1945	1962
Power requirement																		
Power requirement	kW/HP	72/99	84/115	63/85	85/115	85/115	70/95		96/130	96/130	81/110	110/150	103/140	96/130	155/200	168/228	66/90	66/90
Hitching																		
Three-point	category	II + III	II + III	II	II + III	II + III	II+III		II + III	II + III	II	II	II	II	II + III	II + III		
Two-point lower links	category																II	II
Cutting unit																		
Cutting discs	number	8	9	6	6	6	7		7	7	2 x 6	2 x 6	2 x 6	2 x 7	2 x 7	2 x 7	6	6
Blades per mower disc	number	2	2	2	2	2	2		2	2	2	2	2	2	2	2	2	2
Quick-release blade system		■	■	■	■	■	■		■	■	■	■	■	■	■	■	□	□
Compact angle drive		■	■												■	■	■	■
Front wheel drive				■	■	■	■		■	■	■	■	■	■				
DriveGuard		■	■												■	■	■	■
Mechanical lateral displacement											■	■	■	■				
Hydraulic opening/closing of side guard				□	□	□	□		□	□	□	□	□	□				
TurboLift mowing attachment relief		■	■	■	■	■	■		■	■	■	■	■	■	■			
ISOBUS control																■		
SafetySwing				■	■	■	■		■	■					■	■		
EasySwing											■	■	■	■				
BeMove																■		
RC DUO drive						□				□			□					
SectionControl																□		
Hydraulics																		
Required sa hydraulic connections	number	1	1	1	1	1	1		1	1	2	2	2	2	2		1	1
Required da hydraulic connections	number	1	1	1	1	1	1		1	1	1	1	1	1	1		1	1
Required hydraulic connections LS	number															1		
Flat face coupling				□	□	□	□		□	□	□	□	□	□	□	□		
PTO																		
PTO speed	rpm	1000	1000	1000 (850)	1000 (850)	1000 (850)	1000 (850)		1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000	1000	1000	1000
Drive shaft with freewheel		■	■												■	■	■	■
Freilauf im Getriebe				■	■	■	■		■	■	■	■	■	■				
Tyres																		
Transport chassis tyres																	10.0/75-15.3	10.0/75-15.3
Lighting																		
Electrical lighting / warning signs		■	■	□	□	□	□		□	□	■	■	■	■	■	■	■	■
Assembly																		
Assembly time approx.	hrs	1,5	1,5	1,0	1,0	1,0	1,0		1,0	1,0	6,0	7,0	7,0	6,0	8,0	1,0	5,0	5,0