



Equipment variants.*

Technical specifications.

	Power	Power+	Profi	Profi+
Cab				
Radio mounting kit with two stereo speakers	■	■	■	■
Infotainment package	□	□	□	□
Infotainment bundle + 4.1 sound system			□	□
4 camera connections (digital/analogue)	□	□	□	□
4 USB ports			□	□
Radar sensor			□	□

Chassis				
Front axle suspension self-levelling, lockable	☒	☒	☒	☒
Steering brake	☐	☐	☐	☐
Automatic trailer steering axle lock	☐	☐	☐	☐
Compressed air Duomatic coupling	☐	☐	☐	☐

4WD / differential locks

Rear / front differential with 100% disc locking and steering angle sensors	■	■	■	■
---	---	---	---	---

Power lift				
Da front power lift, with external control (separate valve)	☐	☐	☐	☐
Comfort front power lift da, with position control, external controls	☐	☐	☐	☐
Comfort front power lift da, with position control and relief control, external controls	☐	☐	☐	☐
Electrohydraulic power lift da (EHR), with external controls			☐	☐
Hydraulic lower link lateral stabiliser			☐	☐

PTO
Front: 1000 rpm ☐ ☐ ☐ ☐

Hydraulics				
External control for hydraulic control unit at rear	☐	☐	☐	☐
Load sensing system with axial piston pump (109 l/min)	☒	☒	☐	☐
Load sensing system with axial piston pump (152 l/min)	☐	☐	☒	☒
Load sensing system with axial piston pump (193 l/min)	☐	☐	☐	☐
Hydraulic power beyond connection	☐	☐	☐	☐
Return rear	☒	☒	☒	☒
Unpressurised rear return flow	☐	☐	☐	☐
Double connect-under-pressure lever couplings rear	☐	☐	☐	☐
CUP coupling rear	☒	☒	☒	☒
Bio hydraulic oil	☐	☐	☐	☐

Additional equipment				
Manual hitch	☐	☐	☐	☐
Automatic trailer hitch with remote control, rear	☒	☒	☒	☐
Ball coupling, height adjustable	☐	☐	☐	☐
Ball coupling, short, in the bottom hitch	☐	☐	☐	☐
Ball coupling, long, in the bottom hitch	☐	☐	☐	☐
Hitch	☐	☐	☐	☐
Drawbar	☐	☐	☐	☐
Piton-fix	☐	☐	☐	☐
Comfort ballast for front-end weight (not available with front power lift)	☐	☐	☐	☐
Wheel weights, rear wheels	☐	☐	☐	☐
Forced steering (one or two-sided)	☐	☐	☐	☐
Pivoting front wheel mudguard	☒	☒	☒	☒
ABS trailer sockets	☐	☐	☐	☐

Front loader				
Front loader attachment parts	☐	☐	☐	☐
Front loader Cargo 4X/85	☐	☐	☐	☐
Front loader Cargo 5X/85	☐	☐	☐	☐
Front loader Cargo 5X/85 da - third valve		☐	☐	☐
Front loader Cargo 5X/90	☐	☐	☐	☐
Front loader Cargo 5X/90 da - third valve		☐	☐	☐

Transmission and PTO							
Transmission type		ML 140	ML 140	ML 180	ML 180	ML 180	ML 180
Speed range 1	km/h	0,02-28	0,02-28	0,02-28	0,02-28	0,02-28	0,02-28
Speed range 1 - reverse	km/h	0,02-17	0,02-17	0,02-17	0,02-17	0,02-17	0,02-17
Speed range 2	km/h	0,02-50	0,02-50	0,02-50	0,02-50	0,02-50	0,02-50
Speed range 2 - reverse	km/h	0,02-33	0,02-33	0,02-33	0,02-33	0,02-33	0,02-33
Top speed	km/h	50	50	50	50	50	50
Rear PTO		540/ 540E / 1000/ 1000E	540/ 540E / 1000/ 1000E	540/ 540E / 1000/ 1000E	540/ 540E / 1000/ 1000E	540/ 540E / 1000/ 1000E	540/ 540E / 1000/ 1000E
Front PTO option		1000	1000	1000	1000	1000	1000

Tyres							
Front tyres (standard)		480/70R28	540/65R28	540/65R28	540/65R30	540/65R30	540/65R30
Standard tyres rear		580/70R38	650/65R38	650/65R38	650/65R42	650/65R42	650/65R42
1. Optional front tyres		540/65R30	540/65R30	540/65R30	600/65R28	600/65R28	600/65R28
1. Optional rear tyres		580/70R42	580/70R42	650/65R42	710/70R38	710/70R38	710/70R38

Weights							
Unladen weight (base tractor with cab - full tanks, without driver)	kg	7735.0	7735.0	7790.0	7980.0	7980.0	7980.0
Max. permissible overall weight up to 40 km/h country-specific exception approval required	kg	12500.0	12500.0	14000.0	14000.0	14000.0	14000.0
Max. permissible overall weight up to 50 km/h country-specific exception approval required	kg	12500.0	12500.0	14000.0	14000.0	14000.0	14000.0
Max. trailer hitch load	kg	2000.0	2000.0	2000.0	2000.0	2000.0	2000.0

* Please refer to the Settings for equipment variants